

DESIGN DESIGNATION


SB A.A.D.T. - 2023 = 8877
 NB A.A.D.T. - 2023 = 7714
 D.H.V. = 9%
 T = 43%
 V = 70 M.P.H.
 D = 41/59%

FUNCTIONAL CLASSIFICATION- INTERSTATE

NO NEW R/W REQUIRED

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

**PLANS FOR PROPOSED
 STATE HIGHWAY
 VERNON COUNTY**



EXISTING BRIDGE NUMBER	REHABED BRIDGE NUMBER
A1774 (SB)	A17743 (SB)
A1774 (NB)	A17744 (NB)

NOT TO SCALE

NOTE: DASHED OR OPEN SYMBOLS INDICATE EXISTING FEATURES

CONVENTIONAL SYMBOLS
 (USED IN PLANS)

- | | |
|------------------------------|------------|
| EXISTING | NEW |
| BUILDINGS AND STRUCTURES | ————— |
| GUARD RAIL | ———+——— |
| CONCRETE RIGHT-OF-WAY MARKER | ———+——— |
| STEEL RIGHT-OF-WAY MARKER | ———+——— |
| LOCATION SURVEY MARKER | ○ |
| UTILITIES | |
| FIBER OPTICS | -FO- |
| OVERHEAD CABLE TV | -OTV- |
| UNDERGROUND CABLE TV | -UTV- |
| OVERHEAD TELEPHONE | -OT- |
| UNDERGROUND TELEPHONE | -UT- |
| OVERHEAD POWER | -OE- |
| UNDERGROUND POWER | -UE- |
| SANITARY SEWER | -S- |
| STORM SEWER | -SS- |
| GAS | -G- |
| WATER | -W- |
| MANHOLE | ⊕ |
| FIRE HYDRANT | ⊙ |
| WATER VALVE | ⊕ |
| WATER METER | ⊕ |
| DROP INLET | ⊕ |
| DITCH BLOCK | ⊕ |
| GROUND MOUNTED SIGN | ⊕ |
| LIGHT POLE | ⊕ |
| H-FRAME POWER POLE | ⊕ |
| TELEPHONE PEDESTAL | ⊕ |
| FENCE | ⊕ |
| CHAIN LINK | ⊕ |
| WOVEN WIRE | ⊕ |
| GATE POST | ⊕ |
| BENCHMARK | ⊕ |

INDEX OF SHEETS

DESCRIPTION	SHEET NUMBER
TITLE SHEET	1
TYPICAL SECTIONS (TS) (2 SHEETS)	2
QUANTITIES (QU) (5 SHEETS)	3
SPECIAL SHEETS (SS)	4-8
TRAFFIC CONTROL SHEETS (TC)	9-29
EROSION CONTROL SHEETS (EC)	30-32
PAVEMENT MARKING (PM)	33-36
BRIDGE DRAWINGS (B)	
A17743S	1-13
A17744N	1-13

LENGTH OF PROJECT

BEGINNING OF PROJECT	STA. 799 + 60.00
END OF PROJECT	STA. 813 + 93.41
APPARENT LENGTH	1433.41 FEET
EQUATIONS AND EXCEPTIONS: ROADWAY EXCEPTIONS STA 806+91.82 - 807+44.24	-52.42 FEET

TOTAL CORRECTIONS	-52.42 FEET
NET LENGTH OF PROJECT	1380.99 FEET
STATE LENGTH	0.262 MILES
FOR INFORMATION ONLY ESTIMATED DISTURBED ACRES	1.5 ACRES

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL
 JEFFERSON CITY, MO 65102
 1-888-ASK-MODOT (1-888-275-6636)

STATE OF MISSOURI
 PROFESSIONAL ENGINEER
 LICENSE NO. PE-201005763

DATE PREPARED: 10/27/2025
 ROUTE: 149
 STATE: MO
 DISTRICT: SW
 SHEET NO.: 1

COUNTY: VERNON
 JOB NO.: JSR0063
 CONTRACT ID.

PROJECT NO.:
 BRIDGE NO.: A17743, A17744

DATE	DESCRIPTION

REMOVAL OF IMPROVEMENTS

STATION	STATION	OFFSET	ALIGNMENT	ITEM	UNIT	TOTAL	REMARKS
I-49 SOUTHBOUND							
800+44.45	808+44.45	RT	SB I-49	GUARDRAIL	LF	800	SB UPSTREAM INSIDE
807+34.84	808+09.84	RT	SB I-49	GUARDRAIL	LF	75	SB UPSTREAM OUTSIDE
807+93.38	808+13.18	RT	SB I-49	CONC	SY	13	DRAIN BASIN SW CORNER
808+27.93	808+47.83	RT	SB I-49	CONC	SY	13	DRAIN BASIN NW CORNER
808+29.24	808+95.22	RT	SB I-49	CONC	SY	136	SLOPE PROTECTION
811+29.88	811+95.83	RT	SB I-49	CONC	SY	136	SLOPE PROTECTION
811+65.86	811+85.68	RT	SB I-49	CONC	SY	13	DRAIN BASIN SE CORNER
811+69.33	812+44.33	RT	SB I-49	GUARDRAIL	LF	75	SB DOWNSTREAM OUTSIDE
812+00.45	812+20.18	RT	SB I-49	CONC	SY	12	DRAIN BASIN NE CORNER
I-49 NORTHBOUND							
808+67.19	808+87.09	LT	NB I-49	CONC	SY	12	DRAIN BASIN SW CORNER
808+43.26	809+18.26	LT	NB I-49	GUARDRAIL	LF	75	NB DOWNSTREAM OUTSIDE
809+01.68	809+21.62	LT	NB I-49	CONC	SY	13	DRAIN BASIN NW CORNER
809+91.77	809+57.70	LT	NB I-49	CONC	SY	136	SLOPE PROTECTION
811+92.26	812+58.41	LT	NB I-49	CONC	SY	136	SLOPE PROTECTION
812+39.74	812+59.57	LT	NB I-49	CONC	SY	13	DRAIN BASIN SE CORNER
812+43.06	813+18.06	LT	NB I-49	GUARDRAIL	LF	75	NB UPSTREAM INSIDE
812+74.36	812+94.19	LT	NB I-49	CONC	SY	13	DRAIN BASIN NE CORNER
812+77.81	813+52.81	LT	NB I-49	GUARDRAIL	LF	75	NB UPSTREAM OUTSIDE
TOTAL						1 LUMP SUM	

EARTHWORK

STATION	STATION	OFFSET	UNCLASSIFIED EXCAVATION	COMPACTING EMBANKMENT	EMBANKMENT IN PLACE	COMPACTING IN CUT	REMARKS
TEMPORARY CONN 1							
799+60.00	806+91.82	LT I49 MED CL	132	113	559	7.3	TEMP CONN 1 INSTALL
799+60.00	806+91.82	RT I49 MED CL	112	96	604	7.3	TEMP CONN 1 INSTALL
ROUNDING 500CY/MILE			69				
TOTALS			313	209	1163	14.6	

LINEAR GRADING

STATION	STATION	LOC	MODIFIED STA	CLASS 1 STA	CLASS 2 STA	REMARKS
I-49						
799+60.00	806+91.82	MEDIAN	7.3			TEMP CONN 1 OBLIT-SEE SAW CUTS
I-49 SOUTHBOUND						
807+94.24	808+11.00	RT		0.2		CONC APPR PAV'T/SLOPES FOR DRAINAGE
808+11.00	809+00.00	RT		0.9		BRIDGE END GRADING AND MATERIAL REQUIRED
811+25.00	812+05.00	RT		0.8		BRIDGE END GRADING AND MATERIAL REQUIRED
812+05.00	812+19.55	RT		0.2		CONC APPR PAV'T/SLOPES FOR DRAINAGE
I-49 NORTHBOUND						
808+68.07	808+84.00	LT		0.2		CONC APPR PAV'T/SLOPES FOR DRAINAGE
808+84.00	809+60.00	LT		0.8		BRIDGE END GRADING AND MATERIAL REQUIRED
811+92.00	812+82.00	LT		0.9		BRIDGE END GRADING AND MATERIAL REQUIRED
812+82.00	812+93.41	LT		0.2		CONC APPR PAV'T/SLOPES FOR DRAINAGE
TOTAL			7.3	0.8	3.4	

PAVEMENT

STATION	STATION	NET LENGTH FT	AVERAGE WIDTH FT	AREA SF	1.955 TONS/CY	TACK COAT GAL	REMARKS
I-49 SOUTHBOUND							
807+44.24	807+94.24	50.00	46	2300	24.3	25.56	1.75"
812+19.55	812+69.55	50.00	46	2300	24.3	25.56	1.75"
I-49 NORTHBOUND							
807+68.07	808+68.07	100.00	46	4600	55.5	51.11	1.75-2.25"
812+93.41	813+93.41	100.00	46	4600	55.5	51.11	1.75-2.25"
TOTALS				166.1	153.34		
USE				166.1	153		

CONTRACTOR FURNISHED SURVEYING AND STAKING
1 LUMP SUM

MOBILIZATION
1 LUMP SUM

ADDITIONAL MOBILIZATION FOR SEEDING AND MULCHING
EACH
4

TEMPORARY PIPE

STATION	OFFSET	15" LF	REMARKS
I-49			
803+24.83	CL	400	TEMP CONN 1-PIPE INSTALL & REMOVAL
TOTAL		400	

SAW CUTS (INFORMATION ONLY)

STATION	STATION	OFFSET	SAW CUT LF	REMARKS
I-49				
799+60.00		26-30' LT	4.0	NB INSIDE SHOULDER
799+60.00	806+91.82	30' LT	731.8	NB INSIDE SHOULDER
806+91.82		26-30' LT	4.0	NB INSIDE SHOULDER
799+60.00		26-30' RT	4.0	SB INSIDE SHOULDER
799+60.00	806+91.82	30' RT	731.8	SB INSIDE SHOULDER
806+91.82		26-30' RT	4.0	SB INSIDE SHOULDER
799+60.00	806+91.82	26' LT	731.8	TEMP CONN 1 OBLIT
799+60.00	806+91.82	26' RT	731.8	TEMP CONN 1 OBLIT
TOTAL			2943.2	NO DIRECT PAY

MODIFIED COLDMILL

STATION	STATION	LOC	LENGTH FT	WIDTH FT	AREA SF	SY	REMARKS
I-49 SOUTHBOUND							
807+44.24	807+94.24	49' RT	50	46	2300	255.56	
812+19.55	812+69.55	49' RT	50	46	2300	255.56	
I-49 NORTHBOUND							
807+68.07	808+68.07	49' LT	100	46	4600	511.11	
812+93.41	813+93.41	49' LT	100	46	4600	511.11	
TOTAL					1533.34		
USE					1534		

OPTIONAL PAVEMENT

STATION	STATION	NET LENGTH FT	AVERAGE WIDTH FT	AREA SF	9 IN. ASPHALT 81N. PCCP SY	4" TYPE 5 AGG BASE SY	REMARKS
I-49							
799+60.00	806+91.82	731.82	VAR	22257	2473.00	2473.00	TEMP CONN 1 NORTH
TOTALS				2473.00	2473.00	2473.00	
USE				2473.0	2473		

SUMMARY OF QUANTITIES


TEMPORARY EROSION CONTROL						
STATION	STATION	OFFSET	ROCK DITCH CHECK	CURB INLET CHECK	SILT FENCE	REMARKS
			LF	EACH	LF	
I-49 INITIAL PHASE						
800+70.50		CL	20			EX MEDIAN DI TO OUTFALL A
812+60.00		144' LT	10			EX PIPE UNDER RTE 54
814+01.00		CL	10		1.00	MEDIAN DITCH
I-49 CONSTRUCTION PHASE						
805+30.00		CL	10		1.00	UPPER END TEMP PIPE
805+73.00		CL	10		1.00	MEDIAN DITCH
806+16.00		CL	10		1.00	MEDIAN DITCH
806+59.00		CL	10		1.00	MEDIAN DITCH
807+02.00		CL	10		1.00	MEDIAN DITCH
807+45.00		CL	10		1.00	MEDIAN DITCH
807+80.00		170' RT	10		1.00	EX DITCH RT
807+80.00	809+00.00	LT/RT			5.03	
807+88.00		CL	10		1.00	MEDIAN DITCH
808+11.00		72' RT		1	1.00	OUTLET FROM BR A17743S
808+38.00		26' RT		1	1.00	OUTLET FROM BR A17743S
808+78.00		26' LT		1	1.00	OUTLET FROM BR A17744N
809+00.00		167' LT	10		1.00	EX DITCH LT
809+12.00		72' LT		1	1.00	OUTLET FROM BR A17744N
811+77.00		72' RT		1	1.00	OUTLET FROM BR A17743S
811+93.00	812+60.00	LT/RT			4.25	
812+10.00		26' RT		1	1.00	OUTLET FROM BR A17743S
812+52.00		26' LT		1	1.00	OUTLET FROM BR A17744N
812+87.00		72' LT		1	1.00	OUTLET FROM BR A17744N
813+15.00		CL	10		1.00	MEDIAN DITCH
813+58.00		CL	10		1.00	MEDIAN DITCH
TOTALS			150	8	928	
USE			150	8	928	32

CLASS 2 PAVEMENT MARKING PAINT (25-MIL, TYPE 1 BEADS)						
STATION	STATION	OFFSET	6" SOLID WHITE	6" INT WHITE	6" SOLID YELLOW	REMARKS
			LF	LF	LF	
SOUTHBOUND I-49						
785+00.0	848+00.0	30' RT			6300.0	INSIDE EDGELINE
785+00.0	848+00.0	42' RT		1575.0		CENTERLINE
785+00.0	805+64.0	54' RT	2064.0			OUTSIDE EDGELINE
805+64.0	807+64.0	54-66' LT	200.0			EDGELINE TAPER
805+64.0	816+00.0	54' RT		259.0		DOTTED LANELINE-3'LINE 9'GAP
807+64.0	815+60.0	66' RT	796.0			OUTSIDE EDGELINE
816+00.0	816+67.0	54-81' RT	268.0			2-12" GORE LINES
816+67.0	825+70.0	54' RT	903.0			OUTSIDE EDGELINE
825+70.0	826+48.0	54-67' RT	312.0			2-12" GORE LINES
826+48.0	827+00.0	54' RT	104.0			12" GORE LINE
827+00.0	830+00.0	54' RT		75.0		DOTTED LANELINE-3'LINE 9'GAP
827+42.0	834+34.0	66' RT	692.0			OUTSIDE EDGELINE
834+34.0	837+34.0	66-54' RT	300.0			EDGELINE TAPER
837+34.0	848+00.0	54' RT	1066.0			OUTSIDE EDGELINE
NORTHBOUND I-49						
790+97.8	848+00.0	30' LT			5702.2	INSIDE EDGELINE
790+97.8	848+00.0	42' LT		1425.6		CENTERLINE
790+97.8	801+00.0	54' LT	1002.2			OUTSIDE EDGELINE
801+00.0	804+00.0	54-66' LT	300.0			EDGELINE TAPER
804+00.0	818+50.0	54' LT		362.5		DOTTED LANELINE-3'LINE 9'GAP
804+00.0	818+50.0	66' LT	1450.0			OUTSIDE EDGELINE
818+50.0	818+65.0	54' LT	30.0			12" GORE LINE
818+65.0	819+16.0	54-63' LT	204.0			2-12" GORE LINES
819+16.0	827+86.0	54' LT	870.0			OUTSIDE EDGELINE
827+86.0	829+25.0	54-73' LT	556.0			2-12" GORE LINES
829+25.0	833+41.0	54' LT	104.0			DOTTED LANELINE-3'LINE 9'GAP
833+41.0	833+41.0	74-54' LT	416.0			OUTSIDE EDGELINE
833+41.0	848+00.0	54' LT	1459.0			OUTSIDE EDGELINE
TOTALS			12992.2	3801.1	12002.2	
USE			12992.2	3801.1	12003	

SEEDING - COOL SEASON GRASSES
TOTAL ACRES
1.2

TEMPORARY SEEDING
TOTAL ACRES
0.3

MULCHING
TOTAL ACRES
1.5



DATE PREPARED
9/3/2025
ROUTE
149
STATE
MO
DISTRICT
SW
SHEET NO.
3

COUNTY
VERNON
JOB NO.
JSR0063
CONTRACT ID.
PROJECT NO.
BRIDGE NO.

DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)

TEMPORARY ~ CLASS 1 PAVEMENT MARKING PAINT (18-MIL, TYPE P BEADS)

STATION	STATION	OFFSET	LOC	4" WHITE		8" WHITE		SOLID YELLOW		SOLID YELLOW		REMOVAL	REMARKS
				INT LF	LF	LF	LF	LF	LF				
STAGE 2 SB BRIDGE CLOSURES													
784+94.00	793+34.00	54'-42' RT	SB		840							840	REMOVE CL AND PLACE LANE DROP TRANSITION
793+34.00	799+60.00	42' RT	SBL		626							626	REMOVE SOLID AND PLACE INT CL
799+60.00	806+91.82	42' RT-30' LT	SB-NB			1486						743	REMOVE XOVER MARKINGS
799+60.00	806+91.82	30' RT-42' LT	SB-NB				1486					743	REMOVE XOVER MARKINGS
799+60.00	800+60.00	30'-42' LT	NBL				100					100	REMOVE CL AND PLACE END LANE DROP
800+60.00	806+91.82	42' LT	NBL				632					632	DOUBLE SOLID YELLOW
806+91.82	887+00.00	42' LT	NBL				16016					1439	XOVER
887+00.00	894+37.26	42' LT-30' RT	NB-SB					1050				2683	XOVER
887+00.00	893+73.00	30' LT-54' RT	NB-SB									840	REMOVE CL AND PLACE LANE DROP TRANSITION
887+00.00	913+83.00	42' LT	NBL									840	REMOVE CL AND PLACE LANE DROP TRANSITION
913+83.00	922+23.00	42'-30' LT	NBL									840	REMOVE CL AND PLACE LANE DROP TRANSITION
SB BRIDGE COMPLETED AND OPENED TO WINTER TRAFFIC													
784+94.00	793+34.00	42' RT	SB	210								840	REMOVE LANE DROP AND PLACE CL
793+34.00	799+60.00	42' RT	SBL	157								626	REMOVE SOLID AND PLACE INT CL
799+60.00	806+91.82	42' RT-30' LT	SB-NB									743	REMOVE XOVER MARKINGS
799+60.00	806+91.82	30' RT-42' LT	SB-NB									743	REMOVE XOVER MARKINGS
799+60.00	800+60.00	42' LT	NBL	25								100	REMOVE LANE DROP AND PLACE CL
800+60.00	806+91.82	42' LT	NBL	158								632	REMOVE SOLID AND PLACE INT CL
806+91.82	887+00.00	42' LT	NBL	2002								8008	REMOVE DBL YELLOW AND PLACE INT CL
887+00.00	894+37.26	42' LT-30' RT	NB-SB									720	REMOVE XOVER MARKINGS
887+00.00	893+73.00	30' LT-54' RT	NB-SB									525	REMOVE XOVER MARKINGS
887+00.00	913+83.00	42' LT	NBL	671								2683	REMOVE SOLID AND PLACE INT CL
913+83.00	922+23.00	42'-30' LT	NBL	210								840	LANE DROP TRANSITION AND PLACE CL
STAGE 3 NB BRIDGE CLOSURES													
784+94.00	793+34.00	54'-42' RT	SB					840				840	REMOVE CL AND PLACE LANE DROP TRANSITION
793+34.00	806+91.82	42' RT	SBL					1358				1473	XOVER
799+60.00	806+91.82	30' LT-42' RT	SB-NB									1057	XOVER
801+78.00	806+91.82	54' LT-30' RT	SB-NB									16016	DOUBLE SOLID YELLOW
806+91.82	887+00.00	42' RT	SBL									637	END LANE DROP
887+00.00	893+37.26	42' RT	SBL									100	XOVER
893+37.26	894+37.26	42' RT-30' RT	SB-NB					1482				1486	XOVER
887+00.00	894+37.26	30' RT-42' LT	SB-NB									840	REMOVE CL AND PLACE LANE DROP TRANSITION
887+00.00	894+37.26	42' RT-30' LT	SB-NB									840	REMOVE CL AND PLACE LANE DROP TRANSITION
894+37.26	913+83.00	42' LT	NBL					1946				840	REMOVE CL AND PLACE LANE DROP TRANSITION
913+83.00	922+23.00	42'-54' LT	NBL					840				840	REMOVE CL AND PLACE LANE DROP TRANSITION
784+94.00	793+34.00	54'-42' RT	SB									840	REMOVE CL AND PLACE LANE DROP TRANSITION
793+34.00	806+91.82	42' RT	SBL									1358	STAGE 3 MARKINGS
799+60.00	806+91.82	30' LT-42' RT	SB-NB									737	STAGE 3 MARKINGS
801+78.00	806+91.82	54' LT-30' RT	SB-NB									529	STAGE 3 MARKINGS
806+91.82	887+00.00	42' RT	SBL									8008	STAGE 3 MARKINGS
887+00.00	893+37.26	42' RT	SBL									637	STAGE 3 MARKINGS
893+37.26	894+37.26	42' RT-30' RT	SBL									100	STAGE 3 MARKINGS
887+00.00	894+37.26	30' RT-42' LT	SB-NB									741	STAGE 3 MARKINGS
887+00.00	894+37.26	42' RT-30' LT	SB-NB									743	STAGE 3 MARKINGS
894+37.26	913+83.00	42' LT	NBL									1946	STAGE 3 MARKINGS
913+83.00	922+23.00	42'-54' LT	NBL									840	STAGE 3 MARKINGS
TOTAL				3433	4252	5075	39222	5884	36399			36399	
USE					12760		45106		36399				



36 IN. SURFACE-MOUNT DELINEATOR POST				
STATION	STATION	LOC	YELLOW EACH	REMARKS
I-49 WINTER SEASON BETWEEN STAGE 2 & 3				
801+00.00	805+00.00	26' LT	50	NB INSIDE AT 8FT SPACINGS
801+00.00	805+00.00	26' RT	50	SB INSIDE AT 8FT SPACINGS
888+50.00	892+50.00	26' LT	50	NB INSIDE AT 8FT SPACINGS
888+50.00	892+50.00	26' RT	50	SB INSIDE AT 8FT SPACINGS
TOTAL				200

SUMMARY OF QUANTITIES
SHEET 4 OF 5


SIGN	SIZE IN.	AREA SQ. FT.	QTY EACH	TOTAL AREA SQ. FT.	QTY RELOC EACH	TOTAL RELOC SQ. FT.	SIGN NO.	DESCRIPTION
W01-1L	48X48	16.00						TURN (SYMBOL LEFT)
W01-1R	48X48	16.00						TURN (SYMBOL RIGHT)
W01-2L	48X48	16.00						CURVE (SYMBOL LEFT)
W01-2R	48X48	16.00						CURVE (SYMBOL RIGHT)
W01-3L	48X48	16.00						REVERSE TURN (SYMBOL LEFT)
W01-3R	48X48	16.00						REVERSE TURN (SYMBOL RIGHT)
W01-4L	48X48	16.00	4	64.00				REVERSE CURVE (SYMBOL LEFT)
W01-4R	48X48	16.00	4	64.00				REVERSE CURVE (SYMBOL RIGHT)
W01-4BL	48X48	16.00						DOUBLE ARROW REVERSE CURVE (SYMBOL LEFT)
W01-4BR	48X48	16.00						DOUBLE ARROW REVERSE CURVE (SYMBOL RIGHT)
W01-4CL	48X48	16.00						TRIPLE ARROW REVERSE CURVE (SYMBOL LEFT)
W01-4CR	48X48	16.00						TRIPLE ARROW REVERSE CURVE (SYMBOL RIGHT)
W01-6	60X30	12.50	4	50.00				HORIZONTAL ARROW (SYMBOL)
W01-6A	72X36	18.00						HORIZ. ARROW (SYMBOL ON PERMANENT BARRICADE)
W01-7	60X30	12.50						DOUBLE HEAD HORIZONTAL ARROW (SYMBOL)
W01-7A	72X36	18.00						DOUBLE HEAD HORIZ. ARROW (SYMBOL ON PERM. BARR.)
W01-8	18X24	3.00						CHEVRON (SYMBOL)
W01-8A	30X36	7.50						CHEVRON (SYMBOL FOR DIVIDED HIGHWAYS)
W03-1	48X48	16.00						STOP AHEAD (SYMBOL)
W03-2	48X48	16.00						YIELD AHEAD (SYMBOL)
W03-3	48X48	16.00						SIGNAL AHEAD (SYMBOL)
W03-4	48X48	16.00						BE PREPARED TO STOP
W03-5	48X48	16.00						SPEED LIMIT AHEAD
W04-1L	48X48	16.00						MERGE (SYMBOL FROM LEFT)
W04-1R	48X48	16.00						MERGE (SYMBOL FROM RIGHT)
W04-1aL	48X48	16.00	1	16.00				MERGE (LEFT)
W04-1aR	48X48	16.00	1	16.00				MERGE (RIGHT)
W05-1	48X48	16.00	2	32.00				ROAD/BRIDGE/RAMP NARROWS
W05-3	48X48	16.00						ONE LANE BRIDGE
W05-5	48X48	16.00						NARROW LANES
W06-1	48X48	16.00						DIVIDED HIGHWAY END (SYMBOL)
W06-2	48X48	16.00						DIVIDED HIGHWAY END (SYMBOL)
W06-3	48X48	16.00	9	144.00				TWO WAY TRAFFIC (SYMBOL)
W07-3a	30X24	5.00	6	30.00				NEXT XX MILES (PLAQUE)
W08-1	48X48	16.00						BUMP
W08-2	48X48	16.00						DIP
W08-3	48X48	16.00						PAVEMENT ENDS
W08-4	48X48	16.00						SOFT SHOULDER
W08-5	48X48	16.00						SLIPPERY WHEN WET (SYMBOL)
W08-6	48X48	16.00						TRUCK CROSSING
W08-6c	48X48	16.00						TRUCK ENTRANCE
W08-7	36X36	9.00						LOOSE GRAVEL
W08-7a	36X36	9.00						FRESH OIL / LOOSE GRAVEL
W08-9	48X48	16.00						LOW SHOULDER
W08-11	48X48	16.00						UNEVEN LANES
W08-12	48X48	16.00						NO CENTER LINE
W08-15	48X48	16.00						GROOVED PAVEMENT
W08-15B	30X24	5.00						MOTORCYCLE (PLAQUE)
W08-17L	48X48	16.00						SHOULDER DROP-OFF (SYMBOL LEFT)
W08-17R	48X48	16.00						SHOULDER DROP-OFF (SYMBOL RIGHT)
W08-17P	30X24	5.00						SHOULDER DROP-OFF (PLAQUE)
W10-1	42RND.	9.62						RAILROAD CROSSING
W012-1	24X24	4.00						DOUBLE DOWN ARROW (SYMBOL)
W012-2	48X48	16.00						LOW CLEARANCE (SYMBOL)
W012-2x	24X18	3.00						LOW CLEARANCE (PLAQUE)
W012-2a	84X24	14.00						OVERHEAD LOW CLEARANCE (FEET AND INCHES)
W012-4	120X60	50.00						LOW CLEARANCE XX FT XX IN XX MILES AHEAD
W012-5	120X60	50.00						WIDTH RESTRICTION XX FT XX IN XX MILES AHEAD
W013-1	30X30	6.25	4	25.00				ADVISORY SPEED (PLAQUE)
W016-2	30X24	5.00						XXX FEET (PLAQUE)
W016-3	30X24	5.00						X MILE (PLAQUE)
W020-2	48X48	16.00	6	96.00				ROAD/BRIDGE/RAMP WORK AHEAD
W020-3	48X48	16.00	5	80.00				ROAD CLOSED AHEAD
W020-4	48X48	16.00						ONE LANE ROAD AHEAD
W020-5	48X48	16.00	3	48.00				RIGHT/CENTER/LEFT LANE CLOSED AHEAD
W020-5a	48X48	16.00						2 RIGHT/CENTER/LEFT LANES CLOSED AHEAD
W020-6a	48X48	16.00	1	16.00				RIGHT/CENTER/LEFT LANE CLOSED
W020-7a	48X48	16.00						FLAGGER (SYMBOL)
W021-2	36X36	9.00						FRESH OIL
W021-5	48X48	16.00	2	32.00				SHOULDER WORK / SHOULDER WORK AHEAD
W022-1	48X48	16.00						BLASTING ZONE AHEAD
W022-2	42X36	10.50						TURN OFF 2-WAY RADIO AND PHONE
W022-3	42X36	10.50						END BLASTING ZONE
G022-1	21X15	2.19						WET PAINT (ARROW PIVOTS)

SIGN	SIZE IN.	AREA SQ. FT.	QTY EACH	TOTAL AREA SQ. FT.	QTY RELOC EACH	TOTAL RELOC SQ. FT.	SIGN NO.	DESCRIPTION
E05-1	36X48	12.00						GORE EXIT
E05-2	48X36	12.00						EXIT OPEN
E05-2a	48X36	12.00	6	72.00				EXIT CLOSED
G020-1	60X24	10.00	4	40.00				ROAD WORK NEXT XX MILES
G020-2	48X24	8.00	4	32.00				END ROAD WORK
G020-4	36X18	4.50						PILOT CAR FOLLOW ME
G020-4a	42X30	8.75						PILOT CAR IN USE WAIT & FOLLOW
G020-4a	18X12	1.50	24	144.00				PILOT CAR IN USE WAIT & FOLLOW
G020-5aF	36X24	6.00	3	9.00				WORK ZONE (PLAQUE)
M04-8a	24X18	3.00						END DETOUR
M04-9L	48X36	12.00						DETOUR (LEFT)
M04-9R	48X36	12.00						DETOUR (RIGHT)
M04-9P	48X12	4.00						STREET NAME (PLAQUE)
M04-10L	48X18	6.00						DETOUR ARROW (LEFT)
M04-10R	48X18	6.00						DETOUR ARROW (RIGHT)
R1-1	48X48	13.25						STOP
R1-2	48TFL	6.93						YIELD
R1-2a	36X36	9.00						TO ONCOMING TRAFFIC (PLAQUE)
R1-3P	30X12	2.50						ALL WAY (PLAQUE)
R2-1	36X48	12.00	18	216.00				SPEED LIMIT 6-70, 12-60
R3-1	48X48	16.00						NO RIGHT TURN (SYMBOL)
R3-2	48X48	16.00						NO LEFT TURN (SYMBOL)
R3-3	36X36	9.00						NO U-TURN (SYMBOL)
R3-4	48X48	16.00						NO U-TURN (SYMBOL)
R3-7L	30X30	6.25						LEFT LANE MUST TURN LEFT
R3-7R	30X30	6.25						RIGHT LANE MUST TURN RIGHT
R4-1	36X48	12.00	14	168.00				DO NOT PASS
R4-2	36X48	12.00						PASS WITH CARE
R4-7a	36X48	12.00						KEEP RIGHT (HORIZONTAL ARROW)
R4-8a	36X48	12.00						KEEP LEFT (HORIZONTAL ARROW)
R5-1	30X30	6.25	2	12.50				DO NOT ENTER
R5-1a	36X24	6.00						WRONG WAY
R6-1L	54X18	6.75						ONE WAY ARROW (LEFT)
R6-1R	54X18	6.75						ONE WAY ARROW (RIGHT)
R6-2L	24X30	5.00						ONE WAY (LEFT)
R6-2R	24X30	5.00						ONE WAY (RIGHT)
R9-9	24X12	2.00						SIDEWALK CLOSED
R9-11L	24X18	3.00						SIDEWALK CLOSED AHEAD
R10-6	24X36	6.00	3	30.00				SIDEWALK CLOSED AHEAD, (ARROW LEFT) CROSS HERE
R11-2	48X30	10.00						SIDEWALK CLOSED AHEAD, (ARROW RIGHT) CROSS HERE
R11-3a	60X30	12.50						STOP HERE ON RED (45° ARROW)
R11-4	60X30	12.50						ROAD CLOSED XX MILES AHEAD
CONST-3A	60X48	20.00						ROAD CLOSED TO THRU TRAFFIC
CONST-3X	56X12	4.67						FINE SIGN
CONST-5	48X36	12.00	2	24.00				SPEEDING/PASSING (PLATE)
CONST-5	96X48	32.00						POINT OF PRESENCE
CONST-8	48X36	12.00	4	48.00				WORK ZONE NO PHONE ZONE
DETOUR	36X78	19.50	32	624.00				
DETOUR	36X60	15.00	19	285.00				
SPECIAL	48X48	16.00	2	32.00				RUMBLE STRIPS AHEAD
MI								
SC								
ELL								
A								
N								
O								
U								
S								
C								
L								
L								
E								
C								
T								
R								
E								
C								
T								
I								
O								
N								
S								
T								
R								
E								
C								
T								
I								
O								
N								
S								
T								
R								
E								
C								
T								
I								
O								
N								
S								
T								
R								
E								
C								
T								
I								
O								
N								
S								
T								
R								
E								
C								
T								
I								
O								
N								
S								
T								
R								
E								
C								
T								
I								
O								
N								
S								
T								
R								
E								
C								
T								
I								
O								
N								
S								
T								
R								
E								
C								
T								
I								
O								
N								
S								
T								
R								


ANY WORK INDICATED ON THE PLANS THAT EXTENDS BEYOND THE PROJECT LIMITS IS CONSIDERED INCIDENTAL TO AND A PART OF THE CONSTRUCTION OF THIS PROJECT. ALL BEARINGS BASED ON STATE PLANE BEARINGS, WESTERN ZONE. SEE PROJECT JSR0064 FOR TEMPORARY CONNECTION 2, SOUTH OF A1775 BRIDGES.



-  EXIST SHOULDER OBLITERATION INCLUDED IN VOLUME GRADING
-  OPTIONAL PAVEMENT TEMPORARY CONNECTION
-  MODIFIED COLDMILL AND OVERLAY



TEMPORARY CONNECTION 1
NORTH OF A1774 BRIDGES
SPECIAL SHEET
SHEET 1 OF 5



DATE PREPARED	9/3/2025
ROUTE	149
STATE	MO
DISTRICT	SW
SHEET NO.	4

COUNTY
VERNON

JOB NO.
JSR0063

CONTRACT ID.

PROJECT NO.

BRIDGE NO.

DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION





105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)

ROUTE I-49 RT (SOUTHBOUND)

STA. 807+94.24 TO STA. 808+09.24 CONCRETE APPROACH PAVEMENT
 STA. 808+09.24 TO STA. 808+29.24 BRIDGE APPROACH SLAB
 STA. 811+84.55 TO STA. 812+04.55 BRIDGE APPROACH SLAB
 STA. 812+04.55 TO STA. 812+19.55 CONCRETE APPROACH PAVEMENT


SEE STD 609.40 SHEET 3 OF 3
 FOR DRAIN FLUME DETAILS




NOT TO SCALE

NON STANDARD DRAIN FLUME LOCATION

* NOTE: 4" TYPE A CURB REQUIRED ON CONCRETE APPROACH PAVEMENT ON THE SW CORNER OF BRIDGE A17743S, INCIDENTAL TO CONCRETE APPROACH PAVEMENT. TYPE A GUTTER REQUIRED AT CONCRETE APPROACH PAVEMENT ON THE NE CORNER OF BRIDGE A17743S.



DRAIN FLUMES BR A17743S
 SPECIAL SHEET
 SHEET 4 OF 5



DATE PREPARED: 9/3/2025
 ROUTE: 149
 STATE: MO
 DISTRICT: SW
 SHEET NO.: 7

COUNTY: VERNON
 JOB NO.: JSR0063
 CONTRACT ID.:
 PROJECT NO.:
 BRIDGE NO.:

DATE	DESCRIPTION



MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL
 JEFFERSON CITY, MO 65102
 1-888-ASK-MODOT (1-888-275-6636)

ROUTE 1-49 LT (NORTHBOUND)

STA. 808+68.07 TO STA. 808+83.07 CONCRETE APPROACH PAVEMENT
 STA. 808+83.07 TO STA. 809+03.07 BRIDGE APPROACH SLAB
 STA. 812+58.41 TO STA. 812+78.41 BRIDGE APPROACH SLAB
 STA. 812+78.41 TO STA. 812+93.41 CONCRETE APPROACH PAVEMENT


SEE STD 609.40 SHEET 3 OF 3
 FOR DRAIN FLUME DETAILS



NON STANDARD DRAIN FLUME LOCATION

* NOTE: TYPE A GUTTER REQUIRED ON CONCRETE APPROACH PAVEMENT ON THE SW CORNER OF BRIDGE A17744N.

NOT TO SCALE




NON STANDARD DRAIN FLUME LOCATION

* NOTE: TYPE A GUTTER REQUIRED ON CONCRETE APPROACH PAVEMENT ON THE SW CORNER OF BRIDGE A17744N.

NOT TO SCALE

DRAIN FLUMES BR A17744N

SPECIAL SHEET
 SHEET 5 OF 5



DATE PREPARED
 9/3/2025

ROUTE 149
 STATE MO
 DISTRICT SW
 SHEET NO. 8

COUNTY
 VERNON

JOB NO.
 JSR0063

CONTRACT ID.

PROJECT NO.


BRIDGE NO.

DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL
 JEFFERSON CITY, MO 65102
 1-888-ASK-MODOT (1-888-275-6636)

- GENERAL NOTES:
1. ANY EXISTING SIGNS THAT CONFLICT WITH THE TRAFFIC CONTROL SIGNING SHALL BE COMPLETELY COVERED OR REMOVED.
 2. TEMPORARY SIGNING SHOWN IS FOR WORK ON ONE SIDE OF THE ROAD. FOR WORK ON THE OTHER SIDE, REVERSE ORDER OF THE SIGNS AND CHANNELLIZERS.
 3. SIGNING SHOWN SHALL REMAIN IN PLACE UNTIL CONSTRUCTION IS COMPLETE.
 4. ALTERNATE TRAFFIC CONTROL MAY BE USED AS NEEDED AT THE APPROVAL OF THE ENGINEER.
 5. REFER TO STANDARD DRAWING 616.10, 619.10, AND 620.10 FOR ADDITIONAL DETAILS AND 903.03 FOR SIGN AND SIGN MOUNTING REQUIREMENTS.
 6. SPEED LIMIT SIGNS INDICATING THE NORMAL SPEED LIMIT SHALL BE INSTALLED AT THE END OF THE WORK ZONE. PROVIDED NO FURTHER WORK ZONES WILL BE ENCOUNTERED WITHIN THE NEXT 1/2 MILE.
 7. TEMPORARY SPEED LIMIT SIGNS SHALL BE COVERED OR REMOVED WHEN THE CONDITIONS REQUIRING REDUCED SPEEDS DO NOT EXIST.
 8. NO DIRECT PAYMENT WILL BE MADE FOR THE RELOCATION OF CHANNELLIZERS, CONSTRUCTION SIGNS, OR FLASHING ARROW PANEL.
 9. ALL SIGNS, EXCEPT "RATE OUR WORK ZONES" SHALL BE PORTABLE MOUNT AND ARE TO BE MOVED AS WORK PROGRESSES, UNLESS OTHERWISE NOTED. ALL TRAFFIC CONTROL ITEMS SHALL BE REMOVED FROM THE ROADWAY DURING NON-WORKING HOURS.
 10. THE CONTRACTOR SHALL BE RESPONSIBLE FOR IMPLEMENTING AND MAINTAINING PROPER TRAFFIC CONTROL SETUPS THROUGHOUT CONSTRUCTION AS DESCRIBED IN THESE PLANS OR AS APPROVED BY THE ENGINEER.
 11. WHERE MINIMUM LANE WIDTHS CANNOT BE ACHIEVED ON THE SIDE STREETS, THE CONTRACTOR SHALL CLOSE HALF OF THE APPROACH AND POSITION A FLAGGER AT EACH END OF THE WORK AREA. LOCATION TO BE DETERMINED BY THE ENGINEER. ADVANCE FLAGGER SIGNING SHALL BE INSTALLED AS OUTLINED IN THE MUTCD.
 12. THE CONTRACTOR SHALL MAINTAIN PUBLIC ACCESS TO ALL BUSINESSES AND STREETS. NO STREET OR ENTRANCE SHALL BE COMPLETELY BLOCKED.
 13. SPACING & DISTANCES OF TRAFFIC CONTROL DEVICES ARE APPROXIMATE. THE EXACT LOCATIONS SHALL BE DETERMINED IN THE FIELD & APPROVED BY THE ENGINEER.
 14. TRAFFIC CONTROL SHALL CONFORM TO THE LATEST EDITION OF THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD).
 15. ADJUST ADVANCE WARNING SIGN SPACING TO AVOID SIGN PLACEMENT WITHIN THE LIMITS OF THE RAILROAD RIGHT OF WAY.
 16. ALL TRAFFIC CONTROL DEVICES, CONSTRUCTION SIGNS, AND TEMPORARY PAVEMENT MARKING PAID UNDER PROJECT JSR0063.



**TYPICAL BEGINNING AND END OF PROJECT
(DIVIDED HIGHWAY)**


- (1) DISTANCE MAY BE ADJUSTED ACCORDING TO FIELD CONDITIONS. WHERE TRAFFIC BACKUPS ARE EXPECTED BEYOND THE ADVANCE WARNING AREA, ADDITIONAL SIGNING MAY BE NEEDED.
- (2) CONST-5-96 SIGN IS PLACED IN A VISIBLE AREA WITHIN THE PROJECT LIMITS PROVIDED ITS PLACEMENT DOES NOT DISRUPT A SEQUENCE OF SIGNS. IF A VISIBLE LOCATION WITHIN THE PROJECT IS NOT AVAILABLE, THE SIGN MAY BE PLACED 500 FEET BEFORE SIGN CONST-7-72.
- (3) THE "WORK ZONE NO PHONE ZONE" SIGN IS PLACED A MINIMUM OF 500 FEET BEFORE THE ROAD WORK AHEAD SIGN.
- (4) CMS PLACEMENT SHALL BE APPROVED BY THE ENGINEER.



CONST-8
(59) (3)



GO20-1
(1)



WO20-1
(2A)*



WO20-1
(2)

Bridge Improvements

Fall 2026

CONST-5-96

Table of letter and object heights

Letter	Height	Letter	Height	Letter	Height	Letter	Height
A	17.750	B	22.750	C	26.625	D	30.625
E	14.000	F	20.000	G	24.000	H	28.000
I	8.000	J	10.000	K	12.000	L	14.000
M	16.000	N	20.000	O	24.000	P	28.000
Q	12.000	R	16.000	S	20.000	T	24.000
U	10.000	V	14.000	W	18.000	X	22.000
Y	12.000	Z	16.000	1	20.000	2	24.000
3	14.000	4	18.000	5	22.000	6	26.000
7	10.000	8	14.000	9	18.000	0	22.000

Completed as Promised

CONST-5-96

Table of letter and object heights

Letter	Height	Letter	Height	Letter	Height	Letter	Height
A	17.750	B	22.750	C	26.625	D	30.625
E	14.000	F	20.000	G	24.000	H	28.000
I	8.000	J	10.000	K	12.000	L	14.000
M	16.000	N	20.000	O	24.000	P	28.000
Q	12.000	R	16.000	S	20.000	T	24.000
U	10.000	V	14.000	W	18.000	X	22.000
Y	12.000	Z	16.000	1	20.000	2	24.000
3	14.000	4	18.000	5	22.000	6	26.000
7	10.000	8	14.000	9	18.000	0	22.000

NOT TO SCALE
TRAFFIC CONTROL SHEET 1 OF 21



<p>MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION</p> <p>105 WEST CAPITOL JEFFERSON CITY, MO 65102 1-888-ASK-MODOT (1-888-275-6636)</p>	<p>DATE</p> <p>DESCRIPTION</p>	<p>STATE OF MISSOURI</p> <p>SHANNON M. HANCOCK</p> <p>PROFESSIONAL ENGINEER</p> <p>NO. 000000000</p> <p>FE-201005/03</p> <p>DATE PREPARED: 11/26/2024</p> <p>ROUTE: 149</p> <p>STATE: MO</p> <p>DISTRICT: SW</p> <p>SHEET NO.: 9</p> <p>COUNTY: JERSON</p> <p>JOB NO.: JSR0063</p> <p>CONTRACT ID.:</p> <p>PROJECT NO.:</p> <p>BRIDGE NO.:</p>
--	--------------------------------	--

SHOULDER WORK WITH MINOR TRAVELWAY ENCROACHMENT
OR NO ENCROACHMENT
(DIVIDED HIGHWAY)


PERMANENT POSTED (MPH)	DIVIDED HIGHWAYS (S)	TAPER LENGTH (FT)		OPTIONAL BUFFER LENGTH (FT) (B)	CHANNELIZER SPACING (FT)	
		SHOULDER (1) (T1)	LANE (2) (T2)		TAPERS	BUFFER/WORK AREAS
0-35	200	70	245	280	35	40
40-45	500	150	540	400	40	80
50-55	1000	185	660	560	50	80
60-70	SA - 1000 SB - 1500 SC - 2640	235	840	840	60	120

NOTES:

- (1) SHOULDER TAPER LENGTH BASED ON 10 FT. (STANDARD SHOULDER WIDTH) OFFSET.
- (2) LANE TAPER LENGTH BASED ON 12 FT. (STANDARD LANE WIDTH) OFFSET.
- (3) NEXT XX MILES SIGN NOT REQUIRED FOR NARROW LANE SECTIONS LESS THAN ONE MILE.




*OMIT SIGN 43 FOR NO TRAVELWAY ENCROACHMENT.



NOT TO SCALE

TRAFFIC CONTROL SHEET 2 OF 21



DATE PREPARED: 11/26/2024
ROUTE: 149 STATE: MO
DISTRICT: SW SHEET NO.: 10


COUNTY: VERNON
JOB NO.: JSR0063
CONTRACT ID.
PROJECT NO.
BRIDGE NO.

DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)

OUTSIDE LANE CLOSURE



SPEED	SIGN SPACING (FT)	TAPER LENGTH (FT)	CHANNELIZER SPACING (FT)	
			OPTIONAL	WORK AREA
PERMANENT POSTED (MPH)	DIVIDED HIGHWAYS (S)	SHOULDER (1) (T1)	LANE (2) (T2)	LENGTH (FT)
0-35	200	70	245	280
40-45	500	150	540	400
50-55	1000	185	660	560
60-70	SA-1000 SB-1500 SC-2640	235	840	840
				60
				120

NOTES:

(1) SHOULDER TAPER LENGTH BASED ON 10 FT. (STANDARD SHOULDER WIDTH) OFFSET.

(2) LANE TAPER LENGTH BASED ON 12 FT. (STANDARD LANE WIDTH) OFFSET.

SEE BEGIN/END OF PROJECT SIGNING SHEET FOR ADDITIONAL SIGNS.

IN TAPER SECTIONS, QUANTITY OF CHANNELIZERS IS DOUBLED WHEN COMPARED TO MAXIMUM CHANNELIZER SPACING IN CHART.

TEMPORARY PAVEMENT MARKING REQUIRED WITH LONG TERM CLOSURE, NO DIRECT PAY.

NO DIRECT PAYMENT WILL BE MADE FOR RELOCATION OF CHANNELIZERS, SIGNS, AND FLASHING ARROW PANEL.

FOR SHORT TERM OPERATIONS WHERE IT IS NOT FEASIBLE TO MODIFY PAVEMENT MARKING, DEVICE SPACING IS ONE-HALF SPACING SHOWN IN TABLE.

SPEED LIMIT SIGNS INDICATING NORMAL SPEED LIMIT SHALL BE INSTALLED AT END OF THE WORK ZONE. PROVIDED NO FURTHER WORK ZONES WILL BE ENCOUNTERED WITHIN THE NEXT 1/2 MILE.




ALL SIGNS, EXCEPT "RATE OUR WORK ZONE", "NO PHONE ZONE", AND "POINT OF PRESENCE", SHALL BE PORTABLE MOUNT AND ARE TO BE MOVED AS WORK PROGRESSES, UNLESS OTHERWISE NOTED. ALL TRAFFIC CONTROL ITEMS SHALL BE REMOVED FROM THE ROADWAY DURING NON-WORKING HOURS. SEE JOB SPECIAL PROVISIONS.

WORK WILL REQUIRE LANE CLOSURES UNLESS OTHERWISE APPROVED BY THE ENGINEER.

LAYOUT IS TYPICAL FOR EITHER DIRECTION.

SEE STANDARD DRAWING 616.10 FOR ADDITIONAL DETAILS.

PASSING LANE CLOSURE



LONG-TERM RUMBLE STRIPS		
PERMANENT POSTED (MPH)	DISTANCE (FT)	SPACING (FT)
0-45	120	10-12
(OPTIONAL)		
50-55	160	10-12
60-70	200	10-12

TEMPORARY RUMBLE STRIPS SHALL BE ORANGE IN COLOR.


(3) SEE LOCATION IN ABOVE DETAIL DRAWING.

(4) LONG TERM RUMBLE STRIPS SHALL CONSIST OF 5 STRIPS SEPARATED AT 10-12FT CENTERS OR MANUFACTURER'S RECOMMENDATION, WHICHEVER IS LONGER.

NOT TO SCALE

TRAFFIC CONTROL SHEET 3 OF 21

REVISED: 1/9/2024



DATE PREPARED
11/26/2024
ROUTE
149
STATE
MO
DISTRICT
SW
SHEET NO.
11

COUNTY
VERNON
JOB NO.
JSR0063
CONTRACT ID.

PROJECT NO.
BRIDGE NO.

DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION


105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)

INTERIOR LANE CLOSURE ON A FREEWAY

SPEED	SIGN SPACING (FT)	TAPER LENGTH (FT)		OPTIONAL BUFFER LENGTH (FT)	LONGITUDINAL TRANSITION (X)	CHANNELIZER SPACING (FT)	
		SHOULDER (1) (T1)	LANE (2) (T2)			TAPERS	BUFFER/WORK AREAS
0-35		200	70	280	490	35	40
40-45		500	150	400	1080	40	80
50-55		1000	185	560	1320	50	80
60-70		SA - 1000 SB - 1500 SC - 2640	235	840	1680	60	120

NOTES:

- (1) SHOULDER TAPER LENGTH BASED ON 10 FT. (STANDARD SHOULDER WIDTH) OFFSET.
 - (2) LANE TAPER LENGTH BASED ON 12 FT. (STANDARD LANE WIDTH) OFFSET.
- REMOVE AND/OR MODIFY ANY EXISTING PAVEMENT MARKING AS NEEDED.
TEMPORARY PAVEMENT MARKING REQUIRED WITH LONG TERM LANE CLOSURES.



W020-1
(2)

W020-5
(5)

W020-6a
(6)

G020-5ap

W04-1aR
(6B)

W01-4L
(15)


R2-1
(54)
(4)

R2-1
(54)
(4)

R2-1
(25)
(NORMAL SPEED)

NOT TO SCALE

TRAFFIC CONTROL
SHEET 4 OF 21



DATE PREPARED: 11/26/2024
ROUTE: 149
STATE: MO
DISTRICT: SW
SHEET NO.: 12

COUNTY: VERNON
JOB NO.: JSR0063
CONTRACT ID.
PROJECT NO.
BRIDGE NO.


DATE	DESCRIPTION



MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)

DETOUR I 49 SB, RTE 54, RTE K AND LOOP 49
 STAGE 2 - HEAD TO HEAD TRAFFIC IN NB LANES
 SB EXIT 102A AND EXIT 101 CLOSED
 USING HIGHLAND AVE - EXIT 103
 LOOP 49 - EXIT 102B
 NB EXIT 102A
 NB EXIT 101

CHANGEABLE MESSAGE SIGN
 CMS PLACEMENT SHALL BE
 APPROVED BY THE ENGINEER.




-  E05-2a
-  R11-2
-  W020-2
-  M04-8a







LEGEND

- SIGN (SINGLE SIDED)
- ▬ SIGN (DOUBLE SIDED)
- E TYPE 3 MOVEABLE BARRICADE
- ▬ TRAFFIC HEAD TO HEAD IN NB LANES


NOT TO SCALE


-  MO4-8
M3-3
M1-1
M5-1R
73
-  MO4-8
M3-3
M1-1
M6-1
74
-  MO4-8
M3-3
M1-1
M5-1L
75
-  MO4-8
M3-3
M1-1
M6-1
76
-  MO4-8
M3-3
M1-1
M6-3
77
-  MO4-8
M3-3
M1-1
M6-2
78

-  MO4-8
M1-2
M6-3
79
-  MO4-8
M1-2
M6-2
80
-  MO4-8
M1-4
M6-3
83
-  MO4-8
M1-4
M6-2
84
-  MO4-8
M1-5a
M6-3
87
-  MO4-8
M1-5a
M6-2
88

-  MO4-8
M1-5a
M5-1L
89
-  MO4-8
M1-5a
M6-1
90

TRAFFIC CONTROL
 SHEET 5 OF 21

 <p>MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION</p> <p>105 WEST CAPITOL JEFFERSON CITY, MO 65102 1-888-ASK-MODOT (1-888-275-6636)</p>	DATE	DESCRIPTION
 <p>STATE OF MISSOURI PROFESSIONAL ENGINEER NUMBER RE-20105/583 EXPIRES 12/31/2024</p>	DATE PREPARED	11/26/2024
	ROUTE	149
	STATE	MO
	DISTRICT	SW
	SHEET NO.	13
	COUNTY	VERNON
	JOB NO.	JSR0063
	CONTRACT ID.	
	PROJECT NO.	
	BRIDGE NO.	



DATE PREPARED
11/26/2024

ROUTE
149

STATE
MO

DISTRICT
SW

SHEET NO.
14

COUNTY
VERNON

JOB NO.
JSR0063

CONTRACT ID.


PROJECT NO.

BRIDGE NO.

DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION


105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)



MOA-12 SHEET FLAT SHEET FLUORESCENT:
2.250" Radius, 0.875" Border, 0.625" Inset, Black on, Orange:
Table of letter and object lifts

6.000
6.000
6.000
7.500


79



MOA-136 SHEET FLAT SHEET FLUORESCENT:
2.250" Radius, 0.875" Border, 0.625" Inset, Black on, Orange:
Table of letter and object lifts

6.000
6.000
6.000
7.500


78



MOA-136 SHEET FLAT SHEET FLUORESCENT:
2.250" Radius, 0.875" Border, 0.625" Inset, Black on, Orange:
Table of letter and object lifts

6.000
6.000
6.000
7.500


77



MOA-136 SHEET FLAT SHEET FLUORESCENT:
2.250" Radius, 0.875" Border, 0.625" Inset, Black on, Orange:
Table of letter and object lifts

6.000
6.000
6.000
7.500


76



MOA-136 SHEET FLAT SHEET FLUORESCENT:
2.250" Radius, 0.875" Border, 0.625" Inset, Black on, Orange:
Table of letter and object lifts

6.000
6.000
6.000
7.500


75



MOA-136 SHEET FLAT SHEET FLUORESCENT:
2.250" Radius, 0.875" Border, 0.625" Inset, Black on, Orange:
Table of letter and object lifts

6.000
6.000
6.000
7.500


74



MOA-136 SHEET FLAT SHEET FLUORESCENT:
2.250" Radius, 0.875" Border, 0.625" Inset, Black on, Orange:
Table of letter and object lifts

6.000
6.000
6.000
7.500


73



MOA-12 SHEET FLAT SHEET FLUORESCENT:
2.250" Radius, 0.875" Border, 0.625" Inset, Black on, Orange:
Table of letter and object lifts

6.000
6.000
6.000
7.500


90



MOA-17 SHEET FLAT SHEET FLUORESCENT:
2.250" Radius, 0.875" Border, 0.625" Inset, Black on, Orange:
Table of letter and object lifts

6.000
6.000
6.000
7.500


89



MOA-12 SHEET FLAT SHEET FLUORESCENT:
2.250" Radius, 0.875" Border, 0.625" Inset, Black on, Orange:
Table of letter and object lifts

6.000
6.000
6.000
7.500


88



MOA-12 SHEET FLAT SHEET FLUORESCENT:
2.250" Radius, 0.875" Border, 0.625" Inset, Black on, Orange:
Table of letter and object lifts

6.000
6.000
6.000
7.500


87



MOA-12 SHEET FLAT SHEET FLUORESCENT:
2.250" Radius, 0.875" Border, 0.625" Inset, Black on, Orange:
Table of letter and object lifts

6.000
6.000
6.000
7.500


84



MOA-12 SHEET FLAT SHEET FLUORESCENT:
2.250" Radius, 0.875" Border, 0.625" Inset, Black on, Orange:
Table of letter and object lifts

6.000
6.000
6.000
7.500


83




MOA-12 SHEET FLAT SHEET FLUORESCENT:
2.250" Radius, 0.875" Border, 0.625" Inset, Black on, Orange:
Table of letter and object lifts

6.000
6.000
6.000
7.500


80



STAGE 2 - HEAD TO HEAD TRAFFIC TO NORTHBOUND LANES
SOUTHBOUND BRIDGE CLOSURES




WINTER SEASON BETWEEN STAGE 2 & 3
NORMAL TRAFFIC PATTERN NB & SB LANES



TRAFFIC CONTROL LEGEND

- SIGN
- CHANNELIZER
- ◆ TUBULAR MARKER
- ◊ YELLOW TEMP. RAISED PAV'T MARKER
- ◀ WHITE TEMP. RAISED PAV'T MARKER
- ▬ TYPE 3 MOVEABLE BARRICADE
- ▬ DIRECTIONAL BARRICADE W/ SEQUENTIAL LIGHTING
- ▬ TYPE F TEMP. CONCRETE BARRIER
- ▬ WORK AREA
- ▬ ARROW PANEL

TRAFFIC CONTROL SHEET 7 OF 21





DATE PREPARED	11/27/2024
ROUTE	149
STATE	MO
DISTRICT	SW
SHEET NO.	15
COUNTY	VERNON
JOB NO.	JSR0063
CONTRACT ID.	
PROJECT NO.	
BRIDGE NO.	
DATE	
DESCRIPTION	

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)


STAGE 2 - HEAD TO HEAD TRAFFIC TO NORTHBOUND LANES
SOUTHBOUND BRIDGE CLOSURES



TRAFFIC CONTROL LEGEND

- SIGN
- CHANNELLIZER
- TUBULAR MARKER
- YELLOW TEMP. RAISED PAV'T MARKER
- WHITE TEMP. RAISED PAV'T MARKER
- TYPE 3 MOVEABLE BARRICADE
- DIRECTIONAL BARRICADE W/ SEQUENTIAL LIGHTING
- TYPE F TEMP. CONCRETE BARRIER
- WORK AREA
- ARROW PANEL

TRAFFIC CONTROL
SHEET 9 OF 21



THE SHEET HAS BEEN
SEAL, SIGNED AND DATED
IN ACCORDANCE WITH
REQUIREMENTS

DATE PREPARED
11/26/2024

ROUTE
149

STATE
MO

DISTRICT
SW

SHEET NO.
17

COUNTY
VERNON

JOB NO.
JSR0063

CONTRACT ID.

PROJECT NO.




BRIDGE NO.

DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)

STAGE 2 - HEAD TO HEAD TRAFFIC TO NORTHBOUND LANES
SOUTHBOUND BRIDGE CLOSURES



TRAFFIC CONTROL LEGEND

- - SIGN
- - CHANNELIZER
- ◆ - TUBULAR MARKER
- ▽ - YELLOW TEMP. RAISED PAV'T MARKER
- ◀ - WHITE TEMP. RAISED PAV'T MARKER
- ⊞ - TYPE 3 MOVEABLE BARRICADE
- ▲ - DIRECTIONAL BARRICADE W/ SEQUENTIAL LIGHTING
- ▭ - TYPE F TEMP. CONCRETE BARRIER
- ▭ - WORK AREA
- ▭ - ARROW PANEL

TRAFFIC CONTROL
SHEET 10 OF 21

 <p>MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION</p> <p>105 WEST CAPITOL JEFFERSON CITY, MO 65102 1-888-ASK-MODOT (1-888-275-6636)</p>	DATE	DESCRIPTION
<p>STATE OF MISSOURI</p> <p>SHANNON M. HARRIS</p> <p>PROFESSIONAL ENGINEER</p> <p>NO. 201005683</p>	<p>DATE PREPARED</p> <p>11/26/2024</p>	<p>ROUTE</p> <p>149</p> <p>STATE</p> <p>MO</p> <p>DISTRICT</p> <p>SW</p> <p>SHEET NO.</p> <p>18</p>
<p>COUNTY</p> <p>VERNON</p> <p>JOB NO.</p> <p>JSR0063</p> <p>CONTRACT ID.</p> <p>PROJECT NO.</p> <p>BRIDGE NO.</p>	<p>THIS SHEET HAS BEEN APPROVED FOR CONSTRUCTION</p>	<p>DATE PREPARED</p> <p>11/26/2024</p> <p>ROUTE</p> <p>149</p> <p>STATE</p> <p>MO</p> <p>DISTRICT</p> <p>SW</p> <p>SHEET NO.</p> <p>18</p>

905


STAGE 2 - HEAD TO HEAD TRAFFIC TO NORTHBOUND LANES
SOUTHBOUND BRIDGE CLOSURES

910

915



920

930




TRAFFIC CONTROL LEGEND

- - SIGN
- CHANNELLIZER
- ◆ - TUBULAR MARKER
- ▽ - YELLOW TEMP. RAISED PAV'T MARKER
- ◀ - WHITE TEMP. RAISED PAV'T MARKER
- TYPE 3 MOVEABLE BARRICADE
- DIRECTIONAL BARRICADE W/ SEQUENTIAL LIGHTING
- ▬ - TYPE F TEMP. CONCRETE BARRIER
- - WORK AREA
- ▨ - ARROW PANEL



TRAFFIC CONTROL SHEET 12 OF 21



DATE PREPARED 11/26/2024
ROUTE 149
STATE MO
DISTRICT SW
SHEET NO. 20

COUNTY VERNON
JOB NO. JSR0063
CONTRACT ID.



DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)



DETOUR 1-49 NORTH AND SOUTH
STAGE 3 - HEAD TO HEAD IN SB LANES
NB EXIT 101 AND EXIT 102 CLOSED
USING HIGHLAND AVE - EXIT 103
SB EXIT 102A
SB EXIT 101




- EXIT CLOSED** E05-2a (29A)
- ROAD CLOSED** R11-2 (29)
- DETOUR AHEAD** W020-2 (18)
- END DETOUR** MO4-8a (52)

- | | | | | | | | | |
|--|---|--|---|---|---|-----------------------------------|------------------------------------|-----------------------------------|
|
MO4-8
M3-1
M1-1
M5-1R
(63) |
MO4-8
M3-1
M1-1
M6-1
(64) |
MO4-8
M3-1
M1-1
M5-1L
(65) |
MO4-8
M3-1
M1-1
M6-1
(66) |
MO4-8
M3-1
M1-1
M6-3
(67) |
MO4-8
M3-1
M1-1
M6-2
(68) |
MO4-8
M1-4
M6-2
(84) |
MO4-8
M1-4
M5-1L
(85) |
MO4-8
M1-4
M6-1
(86) |
|--|---|--|---|---|---|-----------------------------------|------------------------------------|-----------------------------------|

- | | | |
|------------------------------------|-------------------------------------|------------------------------------|
|
MO4-8
M1-5a
M6-2
(88) |
MO4-8
M1-5a
M5-1L
(89) |
MO4-8
M1-5a
M6-1
(90) |
|------------------------------------|-------------------------------------|------------------------------------|


NBL 1-49 EXISTING SIGNS - USE 29A



LEGEND

- SIGN (SINGLE SIDED)
- ◄◄ SIGN (DOUBLE SIDED)
- E TYPE 3 MOVEABLE BARRICADE
- ▬ TRAFFIC HEAD TO HEAD

NOT TO SCALE




DATE PREPARED 11/26/2024
 ROUTE 149
 STATE MO
 DISTRICT SW
 SHEET NO. 21

COUNTY VERNON
 JOB NO. JSR0063
 CONTRACT ID.
 PROJECT NO.
 BRIDGE NO.

DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION


105 WEST CAPITOL
 JEFFERSON CITY, MO 65102
 1-888-ASK-MODOT (1-888-275-6636)



MO4-11-36 SH-FLAT SHEET FLUORESCENT:
2.250" Radius, 0.875" Border, 0.625" Indent, Black on, Orange:
Interstate 49 12.000" C:
Table of letter and object lifts

6.000	6.000
6.000	6.000
6.000	6.000
7.500	7.500


63



MO4-11-36 SH-FLAT SHEET FLUORESCENT:
2.250" Radius, 0.875" Border, 0.625" Indent, Black on, Orange:
Interstate 49 12.000" C:
Table of letter and object lifts

6.000	6.000
6.000	6.000
6.000	6.000
7.500	7.500


64



MO4-11-36 SH-FLAT SHEET FLUORESCENT:
2.250" Radius, 0.875" Border, 0.625" Indent, Black on, Orange:
Interstate 49 12.000" C:
Table of letter and object lifts

6.000	6.000
6.000	6.000
6.000	6.000
7.500	7.500


65



MO4-11-36 SH-FLAT SHEET FLUORESCENT:
2.250" Radius, 0.875" Border, 0.625" Indent, Black on, Orange:
Interstate 49 12.000" C:
Table of letter and object lifts

6.000	6.000
6.000	6.000
6.000	6.000
7.500	7.500


66



MO4-11-36 SH-FLAT SHEET FLUORESCENT:
2.250" Radius, 0.875" Border, 0.625" Indent, Black on, Orange:
Interstate 49 12.000" C:
Table of letter and object lifts

6.000	6.000
6.000	6.000
6.000	6.000
7.500	7.500


67



MO4-11-36 SH-FLAT SHEET FLUORESCENT:
2.250" Radius, 0.875" Border, 0.625" Indent, Black on, Orange:
Interstate 49 12.000" C:
Table of letter and object lifts

6.000	6.000
6.000	6.000
6.000	6.000
7.500	7.500


68



MO4-12 SH-FLAT SHEET FLUORESCENT:
2.250" Radius, 0.875" Border, 0.625" Indent, Black on, Orange:
Table of letter and object lifts

6.000	6.000
6.000	6.000
6.000	6.000
7.500	7.500


84



MO4-12 SH-FLAT SHEET FLUORESCENT:
2.250" Radius, 0.875" Border, 0.625" Indent, Black on, Orange:
Table of letter and object lifts

6.000	6.000
6.000	6.000
6.000	6.000
7.500	7.500


85



MO4-12 SH-FLAT SHEET FLUORESCENT:
2.250" Radius, 0.875" Border, 0.625" Indent, Black on, Orange:
Table of letter and object lifts

6.000	6.000
6.000	6.000
6.000	6.000
7.500	7.500


86



MO4-12 SH-FLAT SHEET FLUORESCENT:
2.250" Radius, 0.875" Border, 0.625" Indent, Black on, Orange:
Table of letter and object lifts

6.000	6.000
6.000	6.000
6.000	6.000
7.500	7.500


88



MO4-12 SH-FLAT SHEET FLUORESCENT:
2.250" Radius, 0.875" Border, 0.625" Indent, Black on, Orange:
Table of letter and object lifts

6.000	6.000
6.000	6.000
6.000	6.000
7.500	7.500


89




MO4-12 SH-FLAT SHEET FLUORESCENT:
2.250" Radius, 0.875" Border, 0.625" Indent, Black on, Orange:
Table of letter and object lifts

6.000	6.000
6.000	6.000
6.000	6.000
7.500	7.500


90

 <p>MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION</p> <p>105 WEST CAPITOL JEFFERSON CITY, MO 65102 1-888-ASK-MODOT (1-888-275-6636)</p>	DATE	DESCRIPTION	 <p>STATE OF MISSOURI SHANNON M. KEALDER PROFESSIONAL ENGINEER NO. PE-20000003</p>
	<p>DATE PREPARED 11/26/2024</p> <p>ROUTE 149</p> <p>STATE MO</p> <p>DISTRICT SW</p> <p>SHEET NO. 22</p> <p>COUNTY VERNON</p> <p>JOB NO. JSR0063</p> <p>CONTRACT ID.</p> <p>PROJECT NO.</p> <p>BRIDGE NO.</p>		

STAGE 3 - HEAD TO HEAD TRAFFIC TO SOUTHBOUND LANES
NORTHBOUND BRIDGE CLOSURES





TRAFFIC CONTROL LEGEND	
	SIGN
	CHANNELIZER
	TUBULAR MARKER
	YELLOW TEMP. RAISED PAV'T MARKER
	WHITE TEMP. RAISED PAV'T MARKER
	TYPE 3 MOVEABLE BARRICADE
	DIRECTIONAL BARRICADE W/ SEQUENTIAL LIGHTING
	TYPE F TEMP. CONCRETE BARRIER
	WORK AREA
	ARROW PANEL



TRAFFIC CONTROL
SHEET 15 OF 21

<p>MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION</p> <p>105 WEST CAPITOL JEFFERSON CITY, MO 65102 1-888-ASK-MODOT (1-888-275-6636)</p>	DATE	DESCRIPTION
<p>SHANNON M. KEENER REGISTERED PROFESSIONAL ENGINEER PC-2015583</p>	DATE PREPARED	11/26/2024
	ROUTE	149 MO
	DISTRICT	SW
	SHEET NO.	23
	COUNTY	VERNON
JOB NO.	JSR0063	
CONTRACT ID.		
PROJECT NO.		
BRIDGE NO.		


STAGE 3 - HEAD TO HEAD TRAFFIC TO SOUTHBOUND LANES
NORTHBOUND BRIDGE CLOSURES





TRAFFIC CONTROL LEGEND

- SIGN
- CHANNELIZER
- TUBULAR MARKER
- YELLOW TEMP. RAISED PAV'T MARKER
- WHITE TEMP. RAISED PAV'T MARKER
- TYPE 3 MOVEABLE BARRICADE
- DIRECTIONAL BARRICADE W/ SEQUENTIAL LIGHTING
- TYPE F TEMP. CONCRETE BARRIER
- WORK AREA
- ARROW PANEL

TRAFFIC CONTROL
SHEET 16 OF 21

 <p>MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION</p> <p>105 WEST CAPITOL JEFFERSON CITY, MO 65102 1-888-ASK-MODOT (1-888-275-6636)</p>	DATE	DESCRIPTION
 <p>SHANNON M. KEULER PROFESSIONAL ENGINEER NO. 00303 STATE OF MISSOURI</p>	<p>DATE PREPARED 11/26/2024</p> <p>ROUTE 149</p> <p>STATE MO</p> <p>DISTRICT SW</p> <p>SHEET NO. 24</p> <p>COUNTY VERNON</p> <p>JOB NO. JSR0063</p> <p>CONTRACT ID.</p> <p>PROJECT NO.</p> <p>BRIDGE NO.</p>	

STAGE 3 - HEAD TO HEAD TRAFFIC TO SOUTHBOUND LANES
NORTHBOUND BRIDGE CLOSURES




EQUATION:
PT STA 848+85.24 BK
= STA 848+84.67 AHD



TRAFFIC CONTROL LEGEND

- SIGN
- ▬ CHANNELLIZER
- ▬ TUBULAR MARKER
- ▬ YELLOW TEMP. RAISED PAV'T MARKER
- ▬ WHITE TEMP. RAISED PAV'T MARKER
- ▬ TYPE 3 MOVEABLE BARRICADE
- ▬ DIRECTIONAL BARRICADE W/ SEQUENTIAL LIGHTING
- ▬ TYPE F TEMP. CONCRETE BARRIER
- ▬ WORK AREA
- ▬ ARROW PANEL

TRAFFIC CONTROL
SHEET 17 OF 21


 <p>MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION</p> <p>105 WEST CAPITOL JEFFERSON CITY, MO 65102 1-888-ASK-MODOT (1-888-275-6636)</p>	DATE	DESCRIPTION
 <p>STATE OF MISSOURI PROFESSIONAL ENGINEER VERNON LICENSE NUMBER PE-201005783</p>	DATE PREPARED	11/26/2024
	ROUTE	149 MO
	DISTRICT	SW 25
	COUNTY	VERNON
	JOB NO.	JSR0063
PROJECT NO.		
CONTRACT ID.		
BRIDGE NO.		

STAGE 3 - HEAD TO HEAD TRAFFIC TO SOUTHBOUND LANES
NORTHBOUND BRIDGE CLOSURES



TRAFFIC CONTROL LEGEND


- - SIGN
- ▬ - CHANNELIZER
- ◆ - TUBULAR MARKER
- ▽ - YELLOW TEMP. RAISED PAV'T MARKER
- ◀ - WHITE TEMP. RAISED PAV'T MARKER
- ⊥ - TYPE 3 MOVEABLE BARRICADE
- ▴ - DIRECTIONAL BARRICADE W/ SEQUENTIAL LIGHTING
- ▭ - TYPE F TEMP. CONCRETE BARRIER
- ▭ - WORK AREA
- ▭ - ARROW PANEL



TRAFFIC CONTROL
SHEET 18 OF 21



<p>MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION</p> <p>105 WEST CAPITOL JEFFERSON CITY, MO 65102 1-888-ASK-MODOT (1-888-275-6636)</p>	DATE	DESCRIPTION
<p>STATE OF MISSOURI SEAL NUMBER PE-201005763 PROFESSIONAL ENGINEER VERNON SWANN</p>	DATE PREPARED	11/26/2024
<p>ROUTE 149 STATE MO DISTRICT SW SHEET NO. 26</p>		
<p>COUNTY VERNON JOB NO. JSR0063 CONTRACT ID. </p>		
<p>PROJECT NO. </p>		
<p>BRIDGE NO. </p>		

STAGE 3 - HEAD TO HEAD TRAFFIC TO SOUTHBOUND LANES
NORTHBOUND BRIDGE CLOSURES




TRAFFIC CONTROL LEGEND

- SIGN
- CHANNELIZER
- ◆ TUBULAR MARKER
- ▽ YELLOW TEMP. RAISED PAV'T MARKER
- ▲ WHITE TEMP. RAISED PAV'T MARKER
- TYPE 3 MOVEABLE BARRICADE
- DIRECTIONAL BARRICADE W/ SEQUENTIAL LIGHTING
- TYPE F TEMP. CONCRETE BARRIER
- WORK AREA
- ARROW PANEL



TRAFFIC CONTROL SHEET 20 OF 21



DATE PREPARED: 11/26/2024
 ROUTE: 149
 STATE: MO
 DISTRICT: SW
 SHEET NO.: 28

COUNTY: VERNON
 JOB NO.: JSR0063
 CONTRACT ID.
 PROJECT NO.
 BRIDGE NO.

DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL
 JEFFERSON CITY, MO 65102
 1-888-ASK-MODOT (1-888-275-6636)

NOTES:

UPON APPROVAL OF THE ENGINEER, THE CONTRACTOR MAY PROVIDE ADDITIONAL PROTECTIVE TRUCKS EQUIPPED WITH PROPER WARNING DEVICES.

PROTECTIVE TRUCKS AND WORK VEHICLES SHALL DISPLAY HIGH-INTENSITY ROTATING, FLASHING, OSCILLATING, OR STROBE LIGHTS.

VEHICLE HAZARD WARNING SIGNALS SHALL NOT BE USED INSTEAD OF THE VEHICLE'S HIGH-INTENSITY ROTATING, FLASHING, OSCILLATING, OR STROBE LIGHTS.

VEHICLE-MOUNTED SIGNS SHALL BE MOUNTED IN A MANNER SUCH THAT THEY ARE NOT OBSCURED BY EQUIPMENT OR SUPPLIES. SIGN LEGENDS ON VEHICLE-MOUNTED SIGNS SHALL BE COVERED OR TURNED FROM VIEW WHEN WORK IS NOT IN PROGRESS.




FLASHING ARROW PANELS SHALL BE INCIDENTAL TO TRUCK MOUNTED ATTENUATORS, WHEREVER USED. NO ADDITIONAL PAYMENT WILL BE MADE.

FLASHING ARROW PANELS SHALL, AS A MINIMUM, BE TYPE B, WITH A SIZE OF 60 X 30 INCHES.

A FLASHING ARROW BOARD SHALL BE USED WHEN A FREEWAY LANE IS CLOSED. WHEN MORE THAN ONE LANE CLOSED, A SEPARATE FLASHING ARROW BOARD SHALL BE USED FOR EACH CLOSED LANE.

(1) WET PAINT SIGNS ARE INSTALLED TO INDICATE THE SIDE IN WHICH THE PAVEMENT MARKING MATERIAL IS BEING APPLIED. AT THE CONTRACTOR'S OPTION, A FRONT FACING WET PAINT SIGN MAY BE INSTALLED ON THE LEFT SIDE OF THE PAVEMENT MARKING EQUIPMENT.

(2) WARNING TRUCK IS POSITIONED AT THE NO TRACK POINT OF THE PAVEMENT MARKING MATERIAL, OR SPACING SHOWN, WHICH EVER IS GREATER.



SPEED	SPACING
PERMANENT POSTED (MPH)	LENGTH T (FT)
≤ 35	245
40-45	540
50-55	660
60-70	840

SHOULDER ADVANCE WARNING TRUCK WITH WORK SIGNS, FLASHING ARROW PANEL AND REQUIRED TRUCK MOUNTED ATTENUATOR.

WARNING TRUCK WITH WORK SIGNS, FLASHING ARROW PANEL AND REQUIRED TRUCK MOUNTED ATTENUATOR. (2)

WARNING TRUCK WITH WORK SIGNS, FLASHING ARROW PANEL AND REQUIRED TRUCK MOUNTED ATTENUATOR.

PAVEMENT MARKING EQUIPMENT

STRIPING ON MULTI-LANE HIGHWAY

NOT TO SCALE

TRAFFIC CONTROL SHEET 21 OF 21

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION



105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)

DATE	DESCRIPTION

DATE PREPARED: 11/26/2024

ROUTE: 149

DISTRICT: SW

COUNTY: VERNON


JOB NO.: JSR0063

CONTRACT ID:

PROJECT NO.:

BRIDGE NO.:



THIS SHEET HAS BEEN ELECTRONICALLY SIGNED




SHANNON M. KELLER
REGISTERED PROFESSIONAL ENGINEER
NO. 000000083



PERMANENT EROSION CONTROL LEGEND

-  SEEDING LIMITS
-  ROCK DITCH LINER
-  CONC SLOPE PROTECTION



EROSION CONTROL
PERMANENT PHASE
SHEET 3 OF 3

 <p>MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION</p> <p>105 WEST CAPITOL JEFFERSON CITY, MO 65102 1-888-ASK-MODOT (1-888-275-6636)</p>		<p>DATE</p>	<p>DESCRIPTION</p>
 <p>DATE PREPARED 11/26/2024</p> <p>ROUTE 149</p> <p>STATE MO</p> <p>DISTRICT SW</p> <p>SHEET NO. 32</p> <p>COUNTY VERNON</p> <p>JOB NO. JSR0063</p> <p>CONTRACT ID.</p> <p>PROJECT NO.</p> <p>BRIDGE NO.</p>			



THIS SHEET HAS BEEN
REVIEWED AND APPROVED
ELECTRONICALLY

DATE PREPARED
11/26/2024

ROUTE
149

DISTRICT
SW

STATE
MO

SHEET NO.
34

COUNTY
VERNON

JOB NO.
JSR0063

CONTRACT ID.

PROJECT NO.


BRIDGE NO.

DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION



105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)




- PAVEMENT MARKING LEGEND**
- SW - 6" SOLID WHITE LINE
 - LW - 6" INTERMITTENT WHITE LINE (10' MARK, 30' SKIP)
 - SY - 6" SOLID YELLOW LINE
 - DW - 6" DOTTED WHITE LINE (3' MARK, 9' SKIP)
 - GL - 12" WHITE GORE LINE



PAVEMENT MARKING
SHEET 2 OF 4



ROUTE 54



815

820
RAMP 3

825



PAVEMENT MARKING LEGEND

- SW - 6" SOLID WHITE LINE
- LW - 6" INTERMITTENT WHITE LINE (10' MARK, 30' SKIP)
- SY - 6" SOLID YELLOW LINE
- DW - 6" DOTTED WHITE LINE (3' MARK, 9' SKIP)
- GL - 12" WHITE GORE LINE

PAVEMENT MARKING
SHEET 3 OF 4

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION



105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)

DATE	DESCRIPTION

DATE PREPARED	11/26/2024
ROUTE	149
STATE	MO
DISTRICT	35
SHEET NO.	35
COUNTY	VERNON
JOB NO.	JSR0063
CONTRACT ID.	
PROJECT NO.	
BRIDGE NO.	

STATE OF MISSOURI



SEAL OF PROFESSIONAL ENGINEER

NUMBER: PE-2010015783

NAME: SAMUEL M. KENNER

EXPIRES: 11/26/2024

THIS SHEET WAS EITHER PRINTED ELECTRONICALLY OR PHOTOCOPIED



THIS SHEET HAS BEEN
 SUBMITTED TO THE BOARD OF
 PROFESSIONAL ENGINEERS
 ELECTRONICALLY.

DATE PREPARED
 11/26/2024

ROUTE
 149

STATE
 MO

DISTRICT
 SW

SHEET NO.
 36

COUNTY
 VERNON

JOB NO.
 JSR0063

CONTRACT ID.

PROJECT NO.


BRIDGE NO.

DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION



105 WEST CAPITOL
 JEFFERSON CITY, MO 65102
 1-888-ASK-MODOT (1-888-275-6636)




- PAVEMENT MARKING LEGEND
- SW - 6" SOLID WHITE LINE
 - LW - 6" INTERMITTENT WHITE LINE (10' MARK, 30' SKIP)
 - SY - 6" SOLID YELLOW LINE
 - DW - 6" DOTTED WHITE LINE (3' MARK, 9' SKIP)
 - GL - 12" WHITE GORE LINE



U. I. P. AND REDECK EXISTING (57' - 101' - 101' - 57') CONTINUOUS COMPOSITE PLATE GIRDER SPANS (SKEW: 37° L.A.)

SEC/SUR 3 TWP 35 N RGE 31 W



HALF SECTION NEAR MIDSPAN AND END BENT
 TYPICAL SECTION THRU SLAB
 (Conduit in Barrier not shown for clarity)
 HALF SECTION NEAR INT. BENT

General Notes:

Design Specifications:
 2002 AASHTO LFD (17th Ed.) Standard Specifications
 Seismic Performance Category A

Design Loading:

H520-44 (1965 & New Construction)
 35 lb/sf Future Wearing Surface
 Earth - 120 lb/cf, Equivalent Fluid Pressure 45 lb/cf
 Fatigue Stress - Case I

Design Unit Stresses:

Class B-1 Concrete (Barrier) f'c = 4,000 psi
 Class B-2 Concrete (End Bents & Superstructure, except Barrier) f'c = 4,000 psi
 Reinforcing Steel ASTM A615 (Grade 60) fy = 60,000 psi

Joint Filler:

All joint filler shall be in accordance with Sec 1057 for preformed sponge rubber expansion and partition joint filler, except as noted.

Reinforcing Steel:

Minimum clearance to reinforcing steel shall be 1 1/2", unless otherwise shown.

Miscellaneous:

Protective coating for concrete bents and piers (Epoxy) shall be applied as shown on the bridge plans and in accordance with Sec 711.

Bars bonded in existing concrete not removed shall be cleanly stripped and embedded into new concrete where possible. If length is available existing bars shall extend into new concrete at least 40 diameters for plain bars and 30 diameters for deformed bars, unless otherwise noted.

Roadway surfacing adjacent to bridge ends shall match new bridge slab surface. (Roadway Item)

Outline of existing work is indicated by light dashed lines. Heavy lines indicate new work.

Contractor shall verify all dimensions in field before ordering new material.

The area exposed by the removal of concrete and not covered with new concrete shall be coated with an approved qualified special mortar in accordance with Sec 704.

Traffic Handling:

Structure to be closed during construction. See roadway plans for traffic control.

Table Showing S2 and S3 Bar Lengths

Int. Bent No. 2 (S2)	Int. Bent No. 3 (S3)	Int. Bent No. 4 (S2)	Span 1	Span 2	Span 3	Span 4
18'-3"	18'-6"	28'-0"	28'-0"	18'-6"	18'-3"	




Estimated Quantities for Slab on Steel

Item	Total
Class B-2 Concrete	cu. yard 464.0
Reinforcing Steel (Galvanized)	pound 135,820

Required Lap Length For Bar Splices **

Bar Size	Splice Length
4	2'-1"
5	2'-7"
6	3'-1"
7	3'-7"

** Unless otherwise shown.



OPTIONAL SHIFTING TOP BARS AT BARRIER

Estimated Quantities

Item	Total
Removal of Miscellaneous ACM (Non-Friable)	sq. foot 30
Removal of Existing Bridge Deck	sq. foot 15,634
Removal of Existing Bearings	each 6
Bridge Approach Slab (Major)	sq. yard 210
Slab on Steel	sq. yard 1727
Type D Barrier	linear foot 640
Substructure Repair (Formed)	sq. foot 100
Substructure Repair (Unformed)	sq. foot 50
Epoxy Pressure Injecting	linear foot 20
Protective Coating - Concrete Bents and Piers (Epoxy)	linear foot 1
Vertical Drain at End Bents	each 2
Laminated Neoprene Bearing Pad Assembly	each 6

Cost of any required excavation for bridge will be considered completely covered by the contract unit price for other items.

The table of Estimated Quantities for Slab on Steel represents the quantities used by the State in preparing the cost estimate for concrete slabs. The area of the concrete slab will be measured to the nearest square yard longitudinally from end of slab to end of slab and transversely from out to out of bridge slab (or with the horizontal dimensions as shown on the plan of slab). Payment for stay-in-place corrugated steel forms, conventional forms, all concrete and galvanized reinforcing steel will be considered completely covered by the contract unit price for the slab. Variations may be encountered in the estimated quantities but the variations cannot be used for an adjustment in the contract unit price.

Method of forming the slab shall be in accordance with Sec 703. All hardware for forming the slab to be left in place as a permanent part of the structure shall be coated in accordance with ASTM A123 or ASTM B633 with a thickness Class SC 4 and a finish Type I, II or III.

Slab shall be cast-in-place with conventional forming or stay-in-place corrugated steel forms. Precast stressed panels will not be permitted.

For Optional Stay-In-Place Form Details, see Sheet No. 2.

REPAIRS TO BRIDGE:
 INTERSTATE 49 SB OVER US 54 & MNA RR

ROUTE I-49 FROM ROUTE M TO ROUTE K
 ABOUT 4.7 MILES SOUTH OF ROUTE M
 BEGINNING STATION 808+51.89± (MATCH EXISTING)



MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL
 JEFFERSON CITY, MO 65102
 1-888-ASK-MODOT (1-888-275-6636)







STATE OF MISSOURI
 TIMOTHY D. LESE
 PROFESSIONAL ENGINEER
 NUMBER PE-20200778
 LICENSE LESE

DATE	DESCRIPTION

PROJECT NO.	BRIDGE NO.	SHEET NO.

ROUTE	STATE
1-49	MO
DISTRICT	SHEET NO.
BR	1
COUNTY	VERNON
JOB NO.	JSR0063
CONTRACT ID.	
PROJECT NO.	
BRIDGE NO.	A17743



VERTICAL DRAIN AT END BENTS


General Notes:


- All drain pipe shall be sloped 1 to 2 percent.
- Drain pipe may be either 6-inch diameter corrugated metallic-coated steel pipe underdrain, 4-inch diameter corrugated polyvinyl chloride (PVC) drain pipe, or 4-inch diameter corrugated polyethylene (PE) drain pipe.
- Drain pipe shall be placed at fill face of end bent and inside face of wings. The pipe shall slope to lowest grade of ground line, also missing the lower beam of end bent by a minimum of 1 1/2 inches.
- Perforated pipe shall be placed at fill face side and inside face of wings at the bottom of end bent and plain pipe shall be used where the vertical drain ends to the exit at ground line.

Detailed Feb. 2024
 Checked Nov. 2024

Note: This drawing is not to scale. Follow dimensions.

Sheet No. 5 of 13


 <p>MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION</p> <p>105 WEST CAPITOL JEFFERSON CITY, MO 65102 1-888-ASK-MODOT (1-888-275-6636)</p>	DATE	DESCRIPTION
 <p>STATE OF MISSOURI INDEPENDENT PROFESSIONAL ENGINEER NUMBER 178 PERMITS 2000</p>	BRIDGE NO. A17743	PROJECT NO.
ROUTE 1-49 DISTRICT BR COUNTY VERNON JOB NO. JSR0063 CONTRACT ID. PROJECT NO.	DATE PREPARED 2/5/2025	SHEET NO. 5



(1) 2 Spa. @ 12"

U bars and slab bars not shown for clarity.

SECTION NEAR END BENTS



PART PLAN


Note: S bars and Resin Anchors not shown for clarity. Above dimensions taken along \bar{C} of existing bearing from outside face of proposed diaphragm






Notes:
U bars shall clear existing girders by at least 1 1/2 inches.

All concrete and reinforcement in the end bent diaphragm and wings, complete in place, will be considered completely covered by the contract unit price for Slab on Steel, and is included in the Table of Estimated Quantities for Slab on Steel.

The #6-H500 bars are 2 units at 32'-1" with minimum lap of 3'-1". The contractor may use a mechanical bar splice in lieu of a lap splice. When a mechanical bar splice is used, the actual bar segment length will be determined by the contractor to accommodate manufacturer's recommendations for installation and ease of construction. The cost of furnishing and installing the bar splices will be considered completely covered by the contract unit price for Slab on Steel. No adjustment of the quantity of reinforcing steel will be allowed for the use of mechanical bar splices.

DETAILS OF END BENT NO. 5

 <p>MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION</p> <p>105 WEST CAPITOL JEFFERSON CITY, MO 65102 1-888-ASK-MODOT (1-888-275-6636)</p>	DATE	DESCRIPTION
 <p>STATE OF MISSOURI ENGINEER NUMBER PC-201200078 LICENSE PC-201200078 PROFESSIONAL ENGINEER DATE PREPARED 2/5/2025 ROUTE 1-49 STATE MO DISTRICT BR SHEET NO. 6 COUNTY VERNON JOB NO. JSR0063 CONTRACT ID. PROJECT NO. BRIDGE NO. A1743</p>		



** Layers of 1/2" elastomer alternating with 1/8" shim plate

NEOPRENE ELASTOMERIC PAD

SIDE ELEVATION OF BEARING EXTENSION


END ELEVATION OF BEARING EXTENSION

SECTION A-A

PLAN OF BEARING EXTENSION

DETAIL OF ANCHOR ROD WELLS

PLAN OF EXISTING INT. BENT SHOWING ANCHOR RODS





DETAIL OF 3/4" THRU 2 1/2" ANCHOR BOLTS

OPTIONAL DETAIL OF 1 3/8" THRU 2 1/2" ANCHOR BOLTS

SWEDGE ANCHOR BOLT DETAILS

(1) 3/4" for 3/4" thru 1 1/4" anchor bolts
1/2" to 3/4" for 1 3/8" thru 2 1/2" anchor bolts



EXPANSION BEARINGS

BENT NO.	A	B	C	D	E	F	G	J	K	L	M	N	P	Q	R	S	X	NUMBER OF SHIM PLATES *	NUMBER REQUIRED
BENT NO. 2	14"	14"	15 3/8"	25 3/4"	3 3/4"	2 1/8"	10 3/4"	4 1/2"	2 3/4"	14"	1 1/4"	2 7/8"	-	3"	1 1/8"	9 3/8"	1"	4	6
TOTAL BEARINGS																			
6																			


* The required shim plate shall be placed between layers of elastomer and molded together to form an integral unit.

GENERAL NOTES:


- Anchor bolts shall be 2"Ø ASTM F1554 Grade 55 swaged bolts and shall extend 18" into the concrete with ASTM A563 Grade A Heavy Hex nuts. Actual manufacturer's certified mill test reports (chemical and mechanical) shall be provided. Swedging shall be 1" less than extension into the concrete.
- Anchor bolt shall be at the centerline of slotted hole at 60°F. Bearing position shall be adjusted R for each 10° fall or rise in temperature at installation.
- Anchor bolts and heavy hex nuts shall be coated with a minimum of two coats of inorganic zinc primer to provide a total dry film thickness of 4 mils minimum, 6 mils maximum, or galvanized in accordance with Sec 1081.
- Neoprene Elastomeric Pads shall be 60 Durometer.
- Structural steel for sole plate and all bearing extension steel shall be ASTM A709 Grade 50 and shall be coated with a minimum of two coats of inorganic zinc primer to provide a total dry film thickness of 4 mils minimum, 6 mils maximum.
- Laminated Neoprene Bearing Pad Assembly shall be in accordance with Sec 716.
- Cost of bearing extension, complete in place, will be considered completely covered by the contract unit price for Laminated Neoprene Bearing Pad Assembly.
- An equivalent sized W shape may be substituted for the HP14x73 or equivalent size plates may be welded together.
- The required temporary support at Int. Bent No 2 shall be capable of safely supporting a service load of 48 kips/girder (Factor of Load Safety not included). This load includes the dead load (without the slab) and a construction load of 50 psf.
- Retain Bent No: 2 bearings for MODOT Regional Bridge for future use. Deliver to either the Springfield or Nevada Maintenance shed.

LAMINATED NEOPRENE BEARING PAD ASSEMBLY




 <p>MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION</p> <p>105 WEST CAPITOL JEFFERSON CITY, MO 65102 1-888-ASK-MODOT (1-888-275-6636)</p>	<table border="1" style="width: 100%;"> <tr> <th>DATE</th> <th>DESCRIPTION</th> </tr> <tr> <td> </td> <td> </td> </tr> </table> <table border="1" style="width: 100%;"> <tr> <td>PROJECT NO.</td> <td>BRIDGE NO.</td> </tr> <tr> <td> </td> <td>A17743</td> </tr> </table> <table border="1" style="width: 100%;"> <tr> <td>COUNTY</td> <td>VERNON</td> </tr> <tr> <td>JOB NO.</td> <td>JSR0063</td> </tr> <tr> <td>CONTRACT ID.</td> <td> </td> </tr> <tr> <td>PROJECT NO.</td> <td> </td> </tr> </table> <table border="1" style="width: 100%;"> <tr> <td>ROUTE</td> <td>STATE</td> </tr> <tr> <td>I-49</td> <td>MO</td> </tr> <tr> <td>DISTRICT</td> <td>SHEET NO.</td> </tr> <tr> <td>BR 8</td> <td>8</td> </tr> </table> <div style="text-align: right;">  <p>DATE PREPARED: 2/5/2025 MO-PE-2015000778</p> </div>	DATE	DESCRIPTION									PROJECT NO.	BRIDGE NO.		A17743	COUNTY	VERNON	JOB NO.	JSR0063	CONTRACT ID.		PROJECT NO.		ROUTE	STATE	I-49	MO	DISTRICT	SHEET NO.	BR 8	8
DATE	DESCRIPTION																														
PROJECT NO.	BRIDGE NO.																														
	A17743																														
COUNTY	VERNON																														
JOB NO.	JSR0063																														
CONTRACT ID.																															
PROJECT NO.																															
ROUTE	STATE																														
I-49	MO																														
DISTRICT	SHEET NO.																														
BR 8	8																														




ELEVATION OF BARRIER
 (Left barrier shown, right barrier similar)
 Longitudinal dimensions are horizontal.






WATERSTOP DETAIL
 Plastic waterstop shall be placed in all formed joints, except structures with super-elevation, use on lower joints only.
 Cost of plastic waterstop, complete in place, will be considered completely covered by the contract unit price for Type D Barrier.



Use a minimum lap of 3'-1" for #5 horizontal barrier bars. The cross-sectional area above the slab is 3.52 square feet.
 (2) To top of bar



SECTION THRU SAW CUT JOINT



(3) The R1 bar may be separated into two bars as shown, at the contractor's option, only when slip forming is not used. (All dimensions are out to out.)


General Notes:

- * Slip-formed option only.
- Conventional forming or slip forming may be used. Saw cut joints may be used with conventional forming.
- Top of barrier shall be built parallel to grade and barrier joints normal to grade.
- All exposed edges of barrier shall have either a 1/2-inch radius or a 3/8-inch bevel, unless otherwise noted.
- Payment for all concrete and reinforcement, complete in place, will be considered completely covered by the contract unit price for Type D Barrier per linear foot.
- Concrete in barrier shall be Class B-1.
- Measurement of barrier is to the nearest linear foot for each structure, measured along the outside top of slab from end of slab to end of slab.
- Concrete traffic barrier delineators shall be placed on top of the barrier as shown in Missouri Standard Plan 617.10 and in accordance with Sec 617.
- Delineators on bridges with two-lane, two-way traffic shall have retroreflective sheeting on both sides. Concrete traffic barrier delineators will be considered completely covered by the contract unit price for Type D Barrier.
- Joint sealant and backer rods shall be in accordance with Sec 717 for silicone joint sealant for saw cut and formed joints.
- For slip-formed option, both sides of barrier shall have a vertically broomed finish and the top shall have a transversely broomed finish.
- Plastic waterstop shall not be used with saw cut joints.

Detailed Feb. 2024
 Checked Nov. 2024

Note: This drawing is not to scale. Follow dimensions.

TYPE D BARRIER




DATE PREPARED	2/5/2025
ROUTE	I-49
STATE	MO
DISTRICT	BR
SHEET NO.	9
COUNTY	VERNON
JOB NO.	JSR0063
CONTRACT ID.	
PROJECT NO.	
BRIDGE NO.	A17743


MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL
 JEFFERSON CITY, MO 65102
 1-888-ASK-MODOT (1-888-275-6636)

DATE	DESCRIPTION




PART PLAN SHOWING REINFORCEMENT




SECTION A-A

The contractor shall crown the bottom of the approach slab to match the crown of the roadway surface.




SECTION B-B


SECTION C-C




BRIDGE APPROACH SLAB (MAJOR)




UNDERSEAL ACCESS HOLE DETAIL (If required)



CONSTRUCTION JOINT DETAIL




SECTION BETWEEN CURB AND BARRIER



SECTION THRU JOINT AT END OF BRIDGE APPROACH SLAB

SKREW = 37° L.A.

Extend seal full width of approach slab.



DETAILS OF TIMBER HEADER

Remove timber header when concrete pavement is placed.

General Notes:

All concrete for the bridge approach slab and sleeper slab shall be in accordance with Sec 503 (f-c = 4,000 psi).
 The reinforcing steel in the bridge approach slab and the sleeper slab shall be epoxy coated Grade 60 with fy = 60,000 psi.
 Drain pipe may be either 6" diameter corrugated metallic-coated pipe underdrain, 4" diameter corrugated polyvinyl chloride (PVC) drain pipe, or 4" diameter corrugated polyethylene (PE) drain pipe.
 Minimum clearance to reinforcing steel shall be 1 1/2", unless otherwise shown.
 The reinforcing steel in the bridge approach slab and the sleeper slab shall be continuous. The transverse reinforcing steel may be made continuous by providing a minimum lap splice of 29 inches for #5 bars and 44 inches for #6 bars, or by mechanical bar splice.
 Mechanical bar splices shall be in accordance with Sec 710.
 All joint filler shall be in accordance with Sec 1057 for all performed fiber expansion joint filler except as noted.

The contractor shall pour and satisfactorily finish the bridge slab before placing the bridge approach slab.
 Longitudinal construction joints in approach slab and sleeper slab shall be aligned with longitudinal construction joints in bridge slab.
 For concrete approach pavement details, see roadway plans.
 See Missouri Standard Plan 609.00 for details of Type A curb.





Payment for furnishing all materials, labor and excavation necessary to construct the approach slab, including the timber header, sleeper slab, underdrain, Type 5 aggregate base, joint filler and all other appurtenances and incidental work as shown on this sheet, complete in place, will be considered completely covered by the contract unit price for Bridge Approach Slab (Major) per square yard.
 * Seal joint between vertical face of approach slab and wing with sealant in accordance with Sec 717 for silicone joint sealant for saw cut and formed joints.
 Open cell foam joint seal shall be 3" and depth shall be determined by the manufacturer. Manufacturer recommended seal shall meet the movement and installation gap requirements and skew effect.
 The open cell foam joint seal shall be installed according to the manufacturer's recommendations.
 The Open Cell Foam Joint Seal, complete in place, will be considered completely covered by the contract unit price for Bridge Approach Slab (Major).

STATE OF MISSOURI INCH D. REGISTERED PROFESSIONAL ENGINEER NUMBER PC-0000078 VERNON	
ROUTE 1-49	STATE MO
DISTRICT BR	SHEET NO. 11
COUNTY VERNON	JOB NO. JSR0063
CONTRACT ID.	PROJECT NO.
BRIDGE NO. A17743	
DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION



105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)



Finished Bend Diameters D and Hook Dimensions

Standard Pin Bend Shapes

Size Case	D	A or G	H	J
#4	1	3"	8"	6"
#5	1	3 3/4"	10"	7"
#6	1	4 1/4"	12"	8 1/4"
#7	2	5 1/4"	14"	9 3/4"
#8	2	6"	16"	11"
#9	3	8"	17"	13 1/4"
#10	1	10 1/4"	22"	17 1/2"
#11	1	12"	24 1/4"	19 1/4"
#14	1	18 1/4"	31 1/4"	27 1/4"
#18	1	24"	41 1/2"	36 1/4"

Stirrup Pin Bend Shapes (S)

Size Case	D	A or G	H	J
#4	2	4 1/4"	4 1/4"	5"
#5	3	5"	5 1/4"	6"
#6	2	2 1/4"	5 3/4"	5 3/4"
#6	3	3 3/4"	6 1/4"	7"
#6	1	4 1/4"	12"	7 3/4"


Detailing Dimension: 90°

Detailing Dimension: 180°

Detailing Dimension: 90°

Detailing Dimension: 135°

Detailing Dimension: 180°



Reinforcing Steel Totals (Pounds)

Size	Substructure		Superstructure		Entire Bridge		
	Plain	Galv.	Slab	Barrier Form	Plain	Galv.	
By 5	0	0	66,366	17,032	725	0	
Size 6	0	0	67,176	0	0	67,176	
By 7	0	0	2,495	0	0	2,495	
By Type 0	0	0	136,037	17,032	725	0	
Total							153,794

All superstructure reinforcing steel shall be galvanized unless otherwise specified. Products used to repair damaged zinc coating shall not contain aluminum.

All dimensions are out to out. (1) Shall be a deformed or plain spiral bar or wire.

Shapes ending with an S shall be bent in accordance with stirrup pin bend shapes.

Unless otherwise noted, finished bending diameter D is the same for all bends of a shape.

Four angle or channel spacers are required for each column spiral. Spacers are to be placed on inside of spirals. Length and weight of column spirals do not include splices or spacers.

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)


DATE	DESCRIPTION

STATE OF MISSOURI
Professional Engineer
Number 202000778
Date Prepared 2/5/2025


ROUTE 1-49
DISTRICT MO
BR 12

COUNTY VERNON
JOB NO. JSR0063
CONTRACT ID.


PROJECT NO.
BRIDGE NO. A17743




PART PLAN SHOWING PARTIAL CONCRETE REMOVAL AT END BENTS NO. 1 & 5
 (Existing expansion device not shown for clarity)
 (End Bent No. 1 shown, End Bent No. 5 similar)



PART ELEVATION SHOWING PARTIAL CONCRETE REMOVAL AT END BENTS NO. 1 & 5
 (Existing expansion device not shown for clarity)
 (End Bent No. 1 shown, End Bent No. 5 similar)



DETAILS OF CONCRETE REMOVAL AT END BENTS



TYPICAL ELEVATION OF INT. BENTS NO. 3 & 4
 (Normal to railroad)
 (Not to scale)

Notes:

- Asbestos has been detected in the insulation compound between the top of the concrete parapet and the base of the handrail posts. Removal of the handrail and posts, except as shown, is the Contractor's option. Should the Contractor elect to remove the handrail and post, the Contractor will be required to use an Abatement Contractor during the removal. No direct payment will be made for removal of handrail and posts and for asbestos abatement work will be considered choose to perform this work. Cost for the described work will be considered completely covered by the contract unit price for other items in the contract.
- The removal of existing curb, parapet, rails, and end posts as shown will be considered completely covered by the contract price for Remove and Replace Barrier.
- The removal of existing deck concrete as shown will be considered completely covered by the contract unit price for Removal of Existing Expansion Joint and Adjacent Concrete.
- The removal of existing backwall, curtain walls, and wings as shown will be considered completely covered by the contract unit price for Partial Removal of Substructure Concrete.
- Vertical backwall and wingwall reinforcement to be cut off one inch below concrete removal surface and the resulting holes shall be filled with a qualified special mortar.
- A smooth, level surface shall be provided at Bents No. 1 & 5 removal lines.




DATE PREPARED	12/1/2025
ROUTE	I-49
STATE	MO
DISTRICT	BR
SHEET NO.	2
COUNTY	VERNON
JOB NO.	JSR0063
CONTRACT ID.	
PROJECT NO.	
BRIDGE NO.	A1774

DATE	DESCRIPTION


MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL
 JEFFERSON CITY, MO 65102
 1-888-ASK-MODOT (1-888-275-6636)



SECTION NEAR END BENTS

U bars and slab bars not shown for clarity.



PART PLAN

Note: S bars and Resin Anchors not shown for clarity. Above dimensions taken along centerline of existing bearing from outside face of proposed diaphragm.


DETAILS OF END BENT NO. 1

Notes:
U bars shall clear existing girders by at least 1 1/2 inches.

All concrete and reinforcement in the end bent diaphragm and wings, complete in place, will be considered completely covered by the contract unit price for Class B-2 Concrete and Reinforcing Steel (Galvanized), respectively.

The #6-H100 bars are 2 units at 32'-2" with minimum lap of 3'-1". The contractor may use a mechanical bar splice in lieu of a lap splice. When a mechanical bar splice is used, the actual bar segment length will be determined by the contractor to accommodate manufacturer's recommendations for installation and ease of construction. The cost of furnishing and installing the bar splices will be considered completely covered by the contract unit price for Reinforcing Steel (Galvanized). No adjustment of the quantity of reinforcing steel will be allowed for the use of mechanical bar splices.

Work this Sheet with Sheet No. 4.



DATE PREPARED
12/1/2025
ROUTE
1-49
STATE
MO
DISTRICT
BR
COUNTY
VERNON
JOB NO.
JSR0063
CONTRACT ID.


PROJECT NO.
BRIDGE NO.
A17744

DATE	DESCRIPTION


MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION




105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)




DETAILS OF WEB HOLES AT END BENTS



SECTION C-C



SECTION B-B



SECTION A-A

Notes:
Work this sheet with Sheet No. 3.

The exposed and accessible surfaces of the existing structural steel and bearings that will be encased in concrete shall be cleaned with a minimum of SSPC-SP-3 surface preparation and coated with a minimum of one coat of gray epoxy-mastic primer (non-aluminum) in accordance with Sec 1081 to produce a dry film thickness of not less than 3 mils before concrete is poured. The surface preparation and coating for girders shall extend a minimum of one foot outside the face of the girder encasement. Payment for cleaning and coating steel to be encased in concrete will be considered completely covered by the contract unit price for Class B-2 Concrete.

Cost of field drilling holes in existing plate girder webs will be considered completely covered by the contract unit price for Class B-2 Concrete.

The contractor shall use one of the qualified resin anchor systems in accordance with Sec 1039.

Cost of furnishing and installing the resin anchor systems, complete in place, will be considered completely covered by the contract unit price for Class B-2 Concrete.

The minimum embedment depth in concrete with $f'c = 4,000$ psi for the resin anchor systems shall be that required to meet the minimum ultimate pullout strength in accordance with Sec 1039 but shall not be less than 5".


The required temporary support at the end bent shall be capable of safely supporting a service load of 37 kips/girder (factor of load safety not included). This load includes the dead load and a construction load of 50 psf applied to the deck tributary area.

A galvanized #5 Grade 60 reinforcing bar shall be substituted for the 5/8" diameter threaded rod for Resin Anchor System C.


The U bars shall be placed parallel to centerline of roadway.

For details of vertical drain at end bent, see Sheet No. 5.


For details of bridge approach slab, see Sheet No. 11.



DETAIL C JOINT FILLERS AT BEAM STEPS




DETAILS OF RESIN ANCHOR SYSTEM C (30 Req'd. per bent)



DETAIL B

(2) Pr. 5/8"Ø Resin Anchor System C
(3) Manufacturer's recommended embedment length (5" min.)




DETAIL A

DETAILS OF END BENT NO. 1

Detailed May 2024
Checked Nov. 2024

Note: This drawing is not to scale. Follow dimensions.

Sheet No. 4 of 13







PROJECT NO.	BRIDGE NO.	SHEET NO.
VERNON	A17744	4

DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)



VERTICAL DRAIN AT END BENTS

General Notes:


- All drain pipe shall be sloped 1 to 2 percent.
- Drain pipe may be either 6-inch diameter corrugated metallic-coated steel pipe underlain, 4-inch diameter corrugated polyvinyl chloride (PVC) drain pipe, or 4-inch diameter corrugated polyethylene (PE) drain pipe.
- Drain pipe shall be placed at fill face of end bent and inside face of wings. The pipe shall slope to lowest grade of ground line, also missing the lower beam of end bent by a minimum of 1 1/2 inches.
- Perforated pipe shall be placed at fill face side and inside face of wings at the bottom of end bent and plain pipe shall be used where the vertical drain pipe ends to the exit at ground line.


Detailed May 2024
Checked Nov. 2024

Note: This drawing is not to scale. Follow dimensions.

Sheet No. 5 of 13


 <p>MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION</p> <p>105 WEST CAPITOL JEFFERSON CITY, MO 65102 1-888-ASK-MODOT (1-888-275-6636)</p>	DATE	DESCRIPTION

 <p>STATE OF MISSOURI NUMBER PE-20200778 PROFESSIONAL ENGINEER</p>	<p>DATE PREPARED 12/1/2025</p> <p>ROUTE I-49</p> <p>STATE MO</p> <p>DISTRICT BR</p> <p>SHEET NO. 5</p> <p>COUNTY VERNON</p> <p>JOB NO. JSR0063</p> <p>CONTRACT ID.</p> <p>PROJECT NO.</p> <p>BRIDGE NO. A1774</p>
---	---



(1) 2 Spa. @ 12"

Note: U bars and Slab bars not shown for clarity.



PART PLAN


Note: S bars and Resin Anchors not shown for clarity. Above dimensions taken along centerline of existing bearing from outside face of proposed diaphragm.

Notes:
U bars shall clear existing girders by at least 1 1/2 inches.

All concrete and reinforcement in the end bent diaphragm and wings, complete in place, will be considered completely covered by the contract unit price for Class B-2 Concrete and Reinforcing Steel (Galvanized).

The #6-H500 bars are 2 units at 32'-2" with minimum lap of 3'-1". The contractor may use a mechanical bar splice in lieu of a lap splice. When a mechanical bar splice is used, the actual bar segment length will be determined by the contractor to accommodate manufacturer's recommendations for installation and ease of construction. The cost of furnishing and installing the bar splices will be considered completely covered by the contract unit price for Reinforcing Steel (Galvanized). No adjustment of the quantity of reinforcing steel will be allowed for the use of mechanical bar splices.

DETAILS OF END BENT NO. 5



ROUTE 1-49
STATE MO
DISTRICT 6
BR


COUNTY VERNON
JOB NO. JSR0063
CONTRACT ID.

PROJECT NO.
BRIDGE NO. A17744


DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION


105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)




DETAIL OF WEB HOLES
AT END BENTS



SECTION C-C



SECTION B-B



SECTION A-A

Notes:
Work this sheet with Sheet No. 6.

The exposed and accessible surfaces of the existing structural steel and bearings that will be encased in concrete shall be cleaned with a minimum of SSPC-SP-3 surface preparation and coated with a minimum of one coat of gray epoxy-mastic primer (non-aluminum) in accordance with Sec 1039 to produce a dry film thickness of not less than 3 mils before concrete is poured. The surface preparation and coating for girders shall extend a minimum of one foot outside the face of the girder encasement. Payment for cleaning and coating steel to be encased in concrete will be considered completely covered by the contract unit price for Class B-2 Concrete.

Cost of field drilling holes in existing plate girder webs will be considered completely covered by the contract unit price for Class B-2 Concrete.

The contractor shall use one of the qualified resin anchor systems in accordance with Sec 1039.

Cost of furnishing and installing the resin anchor systems, complete in place, will be considered completely covered by the contract unit price for Class B-2 Concrete.


The minimum embedment depth in concrete with $f'c = 4,000$ psi for the resin anchor systems shall be that required to meet the minimum ultimate pullout strength in accordance with Sec 1039 but shall not be less than 5".

The required temporary support at the end bent shall be capable of safely supporting a service load of 37 kips/girder (factor of load safety not included). This load includes the dead load and a construction load of 50 psf applied to the deck tributary area. A galvanized #5 Grade 60 reinforcing bar shall be substituted for the 5/8" \emptyset threaded rod for Resin Anchor System C.

The U bars shall be placed parallel to centerline of roadway.


For details of vertical drain at end bent, see Sheet No. 5.

For details of bridge approach slab, see Sheet No. 11.




DETAIL C
JOINT FILLERS
AT BEAM STEPS

DETAILS OF RESIN ANCHOR SYSTEM C
(30 Req'd. per bent)



DETAIL B

- (2) Pr. -5/8" Resin Anchor System C
- (3) Manufacturer's recommended embedment length (5" min.)




DETAIL A

DETAILS OF END BENT NO. 5

Detailed May 2024
Checked Nov. 2024

Note: This drawing is not to scale. Follow dimensions.

Sheet No. 7 of 13




ROUTE	1-49
STATE	MO
DISTRICT	7
COUNTY	VERNON
JOB NO.	JSR0063
CONTRACT ID.	
PROJECT NO.	
BRIDGE NO.	A17744
SHEET NO.	


DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)




PART PLAN SHOWING REINFORCEMENT




SECTION A-A

SECTION B-B



UNDERSEAL ACCESS HOLE DETAIL (If required)



CONSTRUCTION JOINT DETAIL

All concrete for the bridge approach slab and sleeper slab shall be in accordance with Sec 503 (f'c = 4,000 psi).

The reinforcing steel in the bridge approach slab and the sleeper slab shall be epoxy coated Grade 60 with fy = 60,000 psi.


Drain pipe may be either 6" diameter corrugated metallic-coated pipe underdrain; 4" diameter corrugated polyvinyl chloride (PVC) drain pipe; or 4" diameter corrugated polyethylene (PE) drain pipe.

Minimum clearance to reinforcing steel shall be 1 1/2", unless otherwise shown.


The reinforcing steel in the bridge approach slab and the sleeper slab shall be continuous. The transverse reinforcing steel may be made continuous by providing a minimum lap splice of 29 inches for #5 bars and 44 inches for #6 bars, or by mechanical bar splice.

Mechanical bar splices shall be in accordance with Sec 710.

All joint filler shall be in accordance with Sec 1057 for preformed fiber expansion joint filler except as noted.




SECTION C-C



SECTION BETWEEN CURB AND BARRIER




BRIDGE APPROACH SLAB (MAJOR)



SECTION THRU JOINT AT END OF BRIDGE APPROACH SLAB


SKEW = 37° L.A.

Extend seal full width of approach slab.



DETAILS OF TIMBER HEADER

Remove timber header when concrete pavement is placed.







ROUTE	1-49
STATE	MO
DISTRICT	BR
SHEET NO.	11
COUNTY	VERNON
JOB NO.	JSR0063
CONTRACT ID.	
PROJECT NO.	
BRIDGE NO.	A17744

DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)



BENDING DIAGRAMS

Finished Bend Diameters D and Hook Dimensions

Standard Pin Bend Shapes

Size	Case	D	A or G	90°	180°	180°	J
#4	1	3"	8"	6"	6"	4"	
#5	1	3 3/4"	10"	7"	5"	5"	
#6	1	4 1/4"	12"	8 1/4"	6"	6"	
#7	2	5 1/4"	14"	9 3/4"	7"	7"	
#8	2	6"	16"	11 1/4"	8 3/4"	8"	
#8	3	8"	17"	13 1/4"	10"	10"	
#9	1	9 1/4"	19 1/2"	15 1/2"	11 3/4"	11 3/4"	
#10	1	10 3/4"	22"	17 1/2"	13 1/4"	13 1/4"	
#11	1	12"	24 1/4"	19 1/4"	14 7/8"	14 7/8"	
#14	1	18 1/4"	31 1/4"	27 1/4"	21 5/8"	21 5/8"	
#18	1	24"	41 1/2"	36 1/4"	28 1/2"	28 1/2"	

Stirrup Pin Bend Shapes (S)

Size	Case	D	A or G	90°	135°	180°	135°	180°	H	J
#4	2	2"	4 1/2"	4 1/2"	5"	2 3/8"	3"	3"		
#4	3	3"	5"	5 1/4"	6"	3"	4"	4"		
#5	2	2 1/4"	5 3/4"	5 3/4"	5 3/4"	3 3/8"	3 3/8"	3 3/8"		
#5	3	3 3/8"	6 1/4"	6 1/4"	7"	3 3/8"	5"	5"		
#6	1	4 1/4"	12"	7 3/4"	8 1/4"	4 3/8"	6"	6"		

Detailing Dimension: 90°

Detailing Dimension: 180°


Detailing Dimension: 90°

Detailing Dimension: 135°

Detailing Dimension: 180°

6d for #4 & #5, 12d for #6

Hook A or G



Reinforcing Steel Totals (Pounds)

Size	Substructure		Superstructure		Entire Bridge	
	Plain	Galv.	Slab	Barrier	Slip Form	Plain Galv.
By 5	0	0	5,872	4,479	0	10,351
By 6	0	0	4,252	0	0	4,252
By 7	0	0	2,493	0	0	2,493
By Type	0	0	12,617	4,479	0	17,096

All superstructure reinforcing steel shall be galvanized unless otherwise specified. Products used to repair damaged zinc coating shall not contain aluminum.


All dimensions are out to out. (1) Shall be a deformed or plain spiral bar or wire. Shapes ending with an S shall be bent in accordance with stirrup pin bend shapes. Four angle or channel spacers are required for each column spiral. Spacers are to be placed on inside of spirals. Length and weight of column spirals do not include splices or spacers.

BENDING DIAGRAMS AND REINFORCING STEEL TOTALS

Detailed May 2024
Checked Nov. 2024

Note: This drawing is not to scale. Follow dimensions.

Sheet No. 12 of 13



ROUTE	1-49
STATE	MO
DISTRICT	BR
SHEET NO.	12
COUNTY	VERNON
JOB NO.	JSR0063
CONTRACT ID.	
PROJECT NO.	
BRIDGE NO.	A17744

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)

DATE	DESCRIPTION

DESIGN DESIGNATION

SB A.A.D.T. - 2022 = 8309
 NB A.A.D.T. - 2022 = 8340
 D.H.V. = 8%
 T = 41%
 V = 70 M.P.H.
 D = 49/51%


FUNCTIONAL CLASSIFICATION - INTERSTATE

NO NEW R/W REQUIRED

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

PLANS FOR PROPOSED

**STATE HIGHWAY
 VERNON COUNTY**



CONVENTIONAL SYMBOLS
(USED IN PLANS)

EXISTING	NEW
BUILDINGS AND STRUCTURES	EXISTING
GUARD RAIL	NEW
GUARD CABLE	
CONCRETE RIGHT-OF-WAY MARKER	
STEEL RIGHT-OF-WAY MARKER	
LOCATION SURVEY MARKER	
UTILITIES	
FIBER OPTICS	
OVERHEAD CABLE TV	
UNDERGROUND CABLE TV	
OVERHEAD TELEPHONE	
UNDERGROUND TELEPHONE	
OVERHEAD POWER	
UNDERGROUND POWER	
SANITARY SEWER	
STORM SEWER	
GAS	
WATER	
MANHOLE	
FIRE HYDRANT	
WATER VALVE	
WATER METER	
DROP INLET	
DITCH BLOCK	
GROUND MOUNTED SIGN	
LIGHT POLE	
H-FRAME POWER POLE	
TELEPHONE PEDESTAL	
FENCE	
CHAIN LINK	
WOVEN WIRE	
GATE POST	
BENCHMARK	

NOT TO SCALE

THE EXISTENCE AND APPROXIMATE LOCATION OF UTILITY FACILITIES KNOWN TO EXIST, AS SHOWN ON THE PLANS, ARE BASED ON THE BEST INFORMATION AVAILABLE TO THE COMMISSION AT THIS TIME. THIS INFORMATION IS PROVIDED BY THE COMMISSION "AS-IS" AND THE COMMISSION EXPRESSLY DISCLAIMS ANY REPRESENTATION OR WARRANTY AS TO THE COMPLETENESS, ACCURACY, OR SUITABILITY OF THE INFORMATION FOR ANY USE. RELIANCE UPON THIS INFORMATION IS DONE AT THE RISK AND PERIL OF THE USER, AND THE COMMISSION SHALL NOT BE LIABLE FOR ANY DAMAGES THAT MAY ARISE FROM ANY ERROR IN THE INFORMATION. IT IS, THEREFORE, THE RESPONSIBILITY OF THE CONTRACTOR TO VERIFY THE EXISTENCE, LOCATION AND STATUS OF ANY FACILITY. SUCH VERIFICATION INCLUDES DIRECT CONTACT WITH THE LISTED UTILITIES.

INDEX OF SHEETS

DESCRIPTION	SHEET NUMBER
TITLE SHEET	1
TYPICAL SECTIONS (TS) (2 SHEETS)	2
QUANTITIES (QU) (3 SHEETS)	3
SPECIAL SHEETS (SS)	4-8
EROSION CONTROL SHEETS (EC)	9-14
PAVEMENT MARKING (PM)	15-18
BRIDGE DRAWINGS (B)	
A17751S	1-17
A17752N	1-15

LENGTH OF PROJECT

BEGINNING OF PROJECT	STA. 865 + 18.55
END OF PROJECT	STA. 894 + 37.26
APPARENT LENGTH	2918.71 FEET
EQUATIONS AND EXCEPTIONS: ROADWAY EXCEPTIONS STA 872+21.02 - 887+00.00	-1478.98 FEET

TOTAL CORRECTIONS	-1478.98 FEET
NET LENGTH OF PROJECT	1439.73 FEET
STATE LENGTH	0.273 MILES
FOR INFORMATION ONLY ESTIMATED DISTURBED ACRES	1.6 ACRES

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL
 JEFFERSON CITY, MO 65102
 1-888-ASK-MODOT (1-888-275-6636)


STATE OF MISSOURI
 SHARON H. KENNER
 GOVERNOR
 MISSOURI REGISTERED PROFESSIONAL ENGINEER
 NO. 201005763

DATE PREPARED: 10/27/2025
 ROUTE: 149
 STATE: MO
 DISTRICT: SW
 SHEET NO.: 1

COUNTY: VERNON
 JOB NO.: JSR0064
 CONTRACT ID.
 PROJECT NO.
 BRIDGE NO.

DATE	DESCRIPTION

ASPHALT FACTORS	
COMBINED FACTOR	
SP095C (PG76-22)	1.955 TONS/CY
SP250C (PG64-22)	1.970 TONS/CY
TACK COAT	0.10 GAL/SY
MILLING	



THIS SHEET HAS BEEN
SEAL ELECTRONICALLY.

DATE PREPARED
1/21/2025

ROUTE
149

STATE
MO

DISTRICT
SW

SHEET NO.
2

COUNTY
VERNON

JOB NO.
JSR0064

CONTRACT ID.

PROJECT NO.

BRIDGE NO.


DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION



105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)

UPON REMOVAL OF THE TEMPORARY CONNECTION, LEAVE IN PLACE 4FT OF TEMP CONN PAVEMENT TO SERVE AS NEW PERMANENT MAINLINE SHOULDER AND ADD RUMBLE STRIPS.





STA 887+00.00 TO 890+11.02 NB
STA 891+23.29 TO 894+37.26 NB

STA 890+11.02 TO 891+23.29

STA 887+00.00 TO 890+11.02 SB
STA 891+23.29 TO 894+37.26 SB

SEE PROJECT JSR0063 FOR TEMPORARY CONNECTION 1, NORTH OF A1774 BRIDGES.



THIS SHEET HAS BEEN
APPROVED FOR CONSTRUCTION

DATE PREPARED
11/26/2024

ROUTE
149

STATE
MO

DISTRICT
SW

SHEET NO.
5

COUNTY
VERNON

JOB NO.
JSR0064

CONTRACT ID.

PROJECT NO.


BRIDGE NO.

DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION




105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)




EXIST SHOULDER OBLITERATION INCLUDED IN VOLUME GRADING

OPTIONAL PAVEMENT TEMPORARY CONNECTION



TEMPORARY CONNECTION 2
SOUTH OF A1775 BRIDGES
SPECIAL SHEET
SHEET 2 OF 5



THIS SHEET HAS BEEN
 ELECTRONICALLY
 FILED

DATE PREPARED
 1/21/2025

ROUTE
 149

STATE
 MO

DISTRICT
 SW

SHEET NO.
 6

COUNTY
 VERNON

JOB NO.
 JSR0064

CONTRACT ID.

PROJECT NO.


BRIDGE NO.

DATE	DESCRIPTION


MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION



105 WEST CAPITOL
 JEFFERSON CITY, MO 65102
 1-888-ASK-MODOT (1-888-275-6636)



LINEAR GRADING CLASS 1 PAY LIMITS FOR CONCRETE APPROACH PAVEMENT AND SLOPES FOR DRAINAGE



GRADING LIMITS
 SPECIAL SHEET
 SHEET 3 OF 5



ROUTE I-49 RT (SOUTHBOUND)

STA. 866+18.55 TO STA. 866+33.55 CONCRETE APPROACH PAVEMENT
 STA. 866+33.55 TO STA. 866+53.55 BRIDGE APPROACH SLAB
 STA. 869+61.56 TO STA. 869+81.56 BRIDGE APPROACH SLAB
 STA. 869+81.56 TO STA. 869+96.56 CONCRETE APPROACH PAVEMENT


SEE STD 609.40 SHEET 3 OF 3
 FOR DRAIN FLUME DETAILS

NON STANDARD DRAIN FLUME LOCATION

* NOTE: TYPE A GUTTER REQUIRED ON CONCRETE APPROACH PAVEMENT ON THE
 NE CORNER OF BRIDGE A17751S.



DRAIN FLUMES BR A17751S
 SPECIAL SHEET
 SHEET 4 OF 5





DATE PREPARED 11/26/2024
 ROUTE 149
 STATE MO
 DISTRICT 7
 COUNTY SW
 JOB NO. VERNON
 CONTRACT ID. JSR0064
 PROJECT NO.
 BRIDGE NO.

DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION




105 WEST CAPITOL
 JEFFERSON CITY, MO 65102
 1-888-ASK-MODOT (1-888-275-6636)



- TEMPORARY EROSION CONTROL LEGEND
- CURB INLET CHECK
 - ROCK DITCH CHECK
 - SILT FENCE

NOTE:
EXACT LOCATION OF DITCH CHECKS
AND SILT FENCE TO BE DETERMINED
IN THE FIELD



EROSION CONTROL
INITIAL PHASE
SHEET 1 OF 6


MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION




105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)

DATE	DESCRIPTION


DATE PREPARED	11/26/2024
ROUTE	149
STATE	MO
DISTRICT	9
SW	
COUNTY	VERNON
JOB NO.	JSR0064
CONTRACT ID.	
PROJECT NO.	
BRIDGE NO.	





TEMPORARY EROSION CONTROL LEGEND

-  CURB INLET CHECK
-  ROCK DITCH CHECK
-  SILT FENCE



NOTE:
EXACT LOCATION OF DITCH CHECKS
AND SILT FENCE TO BE DETERMINED
IN THE FIELD

EROSION CONTROL
CONSTRUCTION PHASE
SHEET 3 OF 6


MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION




105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)

DATE	DESCRIPTION

DATE PREPARED	1/21/2025
ROUTE	149
STATE	MO
DISTRICT	SW
SHEET NO.	11
COUNTY	VERNON
JOB NO.	JSR0064
CONTRACT ID.	
PROJECT NO.	
BRIDGE NO.	






845

850

855

STA 848+00
 END PAVEMENT MARKING JSR0063
 BEGIN PAVEMENT MARKING JSR0064


EQ STA 848+85.24 Bk
 = STA 848+84.67 Ahd



- PAVEMENT MARKING LEGEND
- SW - 6" SOLID WHITE LINE
 - LW - 6" INTERMITTENT WHITE LINE (10' MARK, 30' SKIP)
 - SY - 6" SOLID YELLOW LINE
 - DW - 6" DOTTED WHITE LINE (3' MARK, 9' SKIP)
 - GL - 12" WHITE GORE LINE



PAVEMENT MARKING
 SHEET 1 OF 4




DATE PREPARED	11/26/2024
ROUTE	149
STATE	MO
DISTRICT	SW
SHEET NO.	15

COUNTY	VERNON
JOB NO.	JSR0064
CONTRACT ID.	
PROJECT NO.	
BRIDGE NO.	

DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL
 JEFFERSON CITY, MO 65102
 1-888-ASK-MODOT (1-888-275-6636)



THIS SHEET HAS BEEN
 PRINTED ELECTRONICALLY.

DATE PREPARED
 1/21/2025

ROUTE
 149

STATE
 MO

DISTRICT
 SW

SHEET NO.
 16

COUNTY
 VERNON

JOB NO.
 JSR0064

CONTRACT ID.
 PROJECT NO.

BRIDGE NO.

DATE	DESCRIPTION

860

865

870

149 MEDIAN CL
 S 48°25'38"E

NBL I-49

SBL I-49

BRIDGE #A1752N HYDRO

BRIDGE #A1751S HYDRO

RAMP 1

RAMP 2

RAMP 4


LOOP 49

LOOP 49

860+00

859+75

- PAVEMENT MARKING LEGEND
- SW - 6" SOLID WHITE LINE
 - IW - 6" INTERMITTENT WHITE LINE (10' MARK, 30' SKIP)
 - SY - 6" SOLID YELLOW LINE
 - DW - 6" DOTTED WHITE LINE (3' MARK, 9' SKIP)
 - GL - 12" WHITE GORE LINE



PAVEMENT MARKING
 SHEET 2 OF 4

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION



105 WEST CAPITOL
 JEFFERSON CITY, MO 65102
 1-888-ASK-MODOT (1-888-275-6636)



ROUTE K


RAMP 3

875


880

885


RAMP 4



- PAVEMENT MARKING LEGEND**
- SW - 6" SOLID WHITE LINE
 - LW - 6" INTERMITTENT WHITE LINE (10' MARK, 30' SKIP)
 - SY - 6" SOLID YELLOW LINE
 - DW - 6" DOTTED WHITE LINE (3' MARK, 9' SKIP)
 - GL - 12" WHITE GORE LINE



PAVEMENT MARKING
SHEET 3 OF 4



DATE PREPARED	11/26/2024
ROUTE	149
STATE	MO
DISTRICT	SW
SHEET NO.	17

COUNTY
VERNON
JOB NO.
JSR0064
CONTRACT ID.

PROJECT NO.


BRIDGE NO.

DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION



105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)



THIS SHEET HAS BEEN
 REPRODUCED ELECTRONICALLY

DATE PREPARED
 11/26/2024

ROUTE
 149 MO

DISTRICT
 SW 18

COUNTY
 VERNON

JOB NO.
 JSR0064

CONTRACT ID.


PROJECT NO.

BRIDGE NO.

890


895

900



896+00
 END PAVT
 MARKING SB

- PAVEMENT MARKING LEGEND**
- SW - 6" SOLID WHITE LINE
 - LW - 6" INTERMITTENT WHITE LINE (10' MARK, 30' SKIP)
 - SY - 6" SOLID YELLOW LINE
 - DW - 6" DOTTED WHITE LINE (3' MARK, 9' SKIP)
 - GL - 12" WHITE GORE LINE




PAVEMENT MARKING
 SHEET 4 OF 4

<p>MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION</p> <p>105 WEST CAPITOL JEFFERSON CITY, MO 65102 1-888-ASK-MODOT (1-888-275-6636)</p>	DATE	DESCRIPTION


U.I.P. AND REHABILITATE EXISTING (64'-128'-64')
CONTINUOUS COMPOSITE PLATE GIRDER SPANS (SKEW: 50°32'00" L.A.)

38'-0"± Roadway




TYPICAL SECTION THRU EXISTING DECK

PART ELEVATION SHOWING
PLUGGING OF CURB OUTLETS




Notes:


Proposed 1 3/4" Latex Modified Concrete Wearing Surface not shown for clarity.
Cost of labor and materials required to plug existing curb outlets will be considered completely covered by the contract unit price for Curb Blockout.
Estimated material required to fill all curb outlets is 1.1 cubic yards (for information only).




MONOLITHIC DECK REPAIR
REQUIRING INCIDENTAL FORMING



REMOVAL OF EXISTING DECK
REPAIR BEFORE HYDRO DEMOLITION




MONOLITHIC DECK REPAIR
REQUIRING FULL DEPTH REPAIR




MONOLITHIC DECK REPAIR
REQUIRING FULL DEPTH REPAIR

Substructure Repair (Formed) (See Sec 704) Estimate 50 sq. feet at Int. Bent No. 3. Ensure min. 1 1/2" cover to existing reinforcement.



TYPICAL ELEVATION OF
INT. BENTS NO. 2 & 3



DETAIL A

- (1) Removal of existing 3/8"± wearing surface plus 1/2" of existing deck
- (2) 1/2" minimum total surface hydro demolition of sound concrete, measured to mortar line
- (3) 1" vertical side shall be established outside the deteriorated area.
- (4) 1 3/4" minimum Latex Modified Concrete wearing surface
- (5) Original depth of deck minus previous scarification

REPAIRS TO BRIDGE: 1-49 SB OVER ROUTE K


ROUTE 1-49 SB FROM ROUTE 54 TO ROUTE E
ABOUT 1.1 MILES SOUTH OF ROUTE 54
BEGINNING STATION 866+79.99± (Match Existing)

Detailed May 2025
Checked May 2025

Note: This drawing is not to scale. Follow dimensions.

Sheet No. 1 of 17

SEC/SUR 2/11 TWP 35N RGE 31W



DATE PREPARED	10/7/2025
ROUTE	1-49
STATE	MO
DISTRICT	BR
SHEET NO.	1
COUNTY	VERNON
JOB NO.	JSR0064
CONTRACT ID.	
PROJECT NO.	
BRIDGE NO.	A17751

DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)

General Notes :

Design Specifications:
 2002 AASHTO LFD (17th Ed.) Standard Specifications
 Bridge Deck Rating = 5
 Design Loading:
 HS20-44 (1965 & New Construction)
 Design Unit Stresses:
 Class B-2 Concrete (Full Depth Repair & End Bent) f'c = 4,000 psi
 Class B-1 Concrete (Curb Blockout) f'c = 4,000 psi
 Reinforcing Steel (ASTM A615 Grade 60) fy = 60,000 psi
 Structural Carbon Steel (ASTM A709 Grade 36) fy = 36,000 psi

Fabricated Steel Connections:
 Field connections shall be made with 3/4" diameter ASTM F3125 Grade A325 Type 1 bolts and 13/16" diameter holes, except as noted.

Recoating Existing Steel :
 Protective Coating: System G in accordance with Sec 1081.

Surface Preparation: Surface preparation of the existing steel shall be in accordance with Sec 1081 for Recoating of Structural Steel (System G) with Inorganic Zinc Primer. The cost of surface preparation will be considered completely covered by the contract lump sum price for Surface Preparation for Recoating Structural Steel.

Prime Coat: The cost of the prime coat will be considered completely covered by the contract lump sum price for Field Application of Inorganic Zinc Primer.

Field Coats(s): The color of the field coats(s) shall be Gray (Federal Standard #26373). The cost of the intermediate field coat will be considered completely covered by the contract lump sum price for Intermediate Field Coat (System G). The cost of the finish field coat will be considered completely covered by the contract lump sum price for Finish Field Coat (System G).

Limits of Paint Overlap: System G shall overlap the existing coating between 6 inches and 12 inches in order to achieve maximum coverage at the paint limit of each complete system. The final field coating shall be masked to provide crisp, straight lines and to prevent overspray beyond the overlap required.

Coating New Steel:
 Protective Coating: System G in accordance with Sec 1081.

Prime Coat: The cost of the prime coat will be considered completely covered by the contract unit price for the fabricated structural steel.

Field Coats(s): The color of the field coats(s) shall be Gray (Federal Standard #26373). The cost of the intermediate field coat will be considered completely covered by the contract lump sum price for Intermediate Field Coat (System G). The cost of the finish field coat will be considered completely covered by the contract lump sum price for Finish Field Coat (System G).

Miscellaneous:
 At the option of the contractor, the intermediate field coat and finish field coat may be applied in the shop. The contractor shall exercise extreme care during all phases of loading, hauling, handling, erection and pouring of the slab to minimize damage and shall be fully responsible for all repairs and cleaning of the coating systems as required by the engineer.

Miscellaneous:
 The existing vertical clearance shall be maintained during construction when Route K is open to traffic.
 Lane closures on Route I-49 and Route K shall be in accordance with traffic control plans.
 High strength bolts, nuts and washers will be sampled for quality assurance as specified in Sec 106.
 Outline of existing work is indicated by light dashed lines. Heavy lines indicate new work.
 The contractor shall verify all dimensions in field before ordering new material.
 All existing dimensions shown were taken from as-built drawings, or limited field measurements.
 The contractor shall complete a Non-Destructive Test on the connection plate welds at all girder(s) in damaged areas where connection plates will be re-used to confirm suitability of re-use before installing new diaphragm(s). The cost of this work will be considered completely covered by the contract lump sum price for Non-Destructive Testing. See Special Provisions. Required paint removal for this work will be considered completely covered by the lump sum of price for Surface Preparation for Recoating Structural Steel.
 The contractor shall heat straighten the damaged portions of girder(s). The cost of this work will be considered completely covered by the contract lump sum price for Heat Straightening (See Special Provisions).
 Roadway surfacing adjacent to bridge ends shall match new bridge wearing surface (roadway item).
 All joint filler shall be in accordance with Sec 1057 for preformed sponge rubber expansion and partition joint filler, except as noted.
 Minimum clearance to reinforcing steel shall be 1 1/2", unless otherwise shown.
 Bars bonded in existing concrete not removed shall be cleanly stripped and embedded into new concrete where possible. If length is available, existing bars shall extend into new concrete at least 40 diameters for plain bars and 30 diameters for deformed bars, unless otherwise noted.

In order to maintain grade and a minimum thickness of wearing surface as shown on plans it may be necessary to use additional quantities of wearing surface at various locations throughout the structure. The cost of furnishing and installing the wearing surface will be considered completely covered in the contract unit price, including all additional labor, materials or equipment for variations in thickness of wearing surface.

Substructure Repair:

Provide a minimum 1 1/2" clear cover to existing reinforcing steel when forming substructure repairs at columns.

All concrete repairs shall be in accordance with Sec 704, unless otherwise noted.

Traffic Handling:

Structure to be closed during construction. See roadway plans for traffic control.

Estimated Quantities

Item		Total
** Removal of Miscellaneous ACM (Non-Friable)	sq. foot	28
Total Surface Hydro Demolition	sq. yard	1083
Removal of Asphalt Wearing Surface	sq. foot	9747
Removal of Existing Deck Repair	sq. foot	400
Partial Removal of Substructure Concrete	Lump sum	1
Removal of Existing Expansion Joint & Adjacent Concrete	linear foot	60
Removal of Existing Bearings	each	5
Remove and Replace Barrier	linear foot	9
Bridge Approach Slab (Major)	sq. yard	170
* Supplementary Wearing Surface Material	cu. yard	18
Late Modified Concrete Wearing Surface	sq. yard	1085
Diamond Grinding	sq. yard	1085
Class B-2 Concrete	cu. yard	72.9
Curb Blockout	linear foot	588
Substructure Repair (Formed)	sq. foot	100
Full Depth Repair	sq. foot	500
Cleaning and Epoxy Coating	sq. foot	1856
Reinforcing Steel (Galvanized)	pounds	4030
Protective Coating - Concrete Bents and Piers (Epoxy)	Lump sum	1
Fabricated Structural Carbon Steel (Misc.)	pounds	790
Drainage System (On Structure)	Lump sum	1
Surface Preparation for Recoating Structural Steel	sq. foot	2400
Field Application of Inorganic Zinc Primer	sq. foot	2400
Intermediate Field Coat (System G)	sq. foot	2400
Finish Field Coat (System G)	sq. foot	2400
Heat Straightening	Lump sum	1
Cored Slab Drains	each	37
Vertical Drain at End Bents	each	2
Laminated Neoprene Bearing Pad Assembly	each	5
Misc. Installation of Bearings (pre-owned)	each	5

* Supplementary wearing surface material will be paid for at the fixed unit price in accordance with Sec 109.

** Cost of removal of aluminum tube railing will be considered completely covered by the contract unit price for Removal of Miscellaneous ACM (Non-Friable).




MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION


105 WEST CAPITOL JEFFERSON CITY, MO 65102
 1-888-ASK-MODOT (1-888-275-6636)

DATE	DESCRIPTION


BRIDGE NO.	A17751
PROJECT ID.	JSR0064
JOB NO.	VERNON
COUNTY	MO
ROUTE	I-49
DISTRICT	BR
SHEET NO.	2
DATE PREPARED	10/7/2025
NUMBER	PC-201200778
PROJ. EST. NO.	PC-201200778
ISSUED BY	




PART ELEVATION SHOWING LIMITS OF PAINT OVERLAP
(Vertical or horizontal paint limit.
Horizontal limit shown)




TYPICAL ELEVATION AT END BENT NO. 4
Barrier end post and aluminum tube railing removal and proposed curb blockout not shown for clarity.




PART PLAN SHOWING PARTIAL CONCRETE REMOVAL AT END BENT NO. 4
Existing expansion device armor not shown for clarity



TYPICAL SECTION THRU END BENT NO. 1




DETAIL A SHOWING RESIN ANCHOR SYSTEM F
(59 req'd)



DETAIL OF RESIN ANCHOR SYSTEM E
(58 req'd per End Bent)

Notes:

- Resin Anchor System E shall be a 5/8"Ø threaded rod with flat washer and two heavy hex nuts (burr threads to prevent loosening). All hardware for Resin Anchor System E shall be galvanized in accordance with ASTM A153.
- A galvanized #5 Grade 60 reinforcing bar shall be substituted for the 5/8"Ø threaded rod for Resin Anchor System F.
- The contractor shall use one of the qualified Resin Anchor Systems in accordance with Sec 1039.
- Cost of furnishing and installing Resin Anchor Systems E and F, complete in place, will be considered completely covered by the contract unit price for Class B-2 Concrete.
- The minimum embedment depth in concrete with f'c = 4,000 psi for the resin anchor systems shall be that required to meet the minimum ultimate pullout strength in accordance with Sec 1039 but shall not be less than 5".
- The removal of existing deck concrete as shown on Sheet No. 3 will be considered completely covered by the contract unit price for Removal of Existing Expansion Joint and Adjacent Concrete.
- The removal of existing curtain walls will be considered completely covered by the contract unit price for Partial Removal of Substructure Concrete.
- Vertical backwall and curtain wall reinforcement to be cut off one inch below concrete removal surface and the resulting holes shall be filled with a qualified special mortar.
- A smooth, level surface shall be provided at Bent No. 4 removal lines.
- The removal of existing curb, parapet, and rails as shown 3 will be considered completely covered by the contract price for Remove and Replace Barrier.



DATE PREPARED
10/7/2025
ROUTE
1-49
STATE
MO
DISTRICT
BR
SHEET NO.
3


COUNTY
VERNON
JOB NO.
JSR0064
CONTRACT ID.

PROJECT NO.
BRIDGE NO.
A17751


DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)




U bars and slab reinforcement not shown for clarity.




(1) 2 Spa. @ 12"

PART PLAN

Slab reinforcement and resin anchors not shown for clarity.
Above dimensions taken along \mathcal{C} of existing bearing
From outside face of proposed slab.



DETAIL C
All dimensions are plus/minus.



DETAIL D
All dimensions are plus/minus.

Notes:

Work this Sheet with Sheet No. 5.

The exposed and accessible surface of the existing structural steel and bearing that will be encased in concrete shall be cleaned with a minimum of SSPC-SP-3 surface preparation and coated with a minimum of one coat of gray epoxy-mastic primer (non-aluminum) in accordance with Sec. 1081 to produce a dry fill thickness of not less than 3 mils before concrete is poured. The surface preparation and coating for girders shall extend a minimum of one foot outside the face of the beam encasement. Payment for cleaning and coating steel to be encased in concrete will be considered completely covered by the contract unit price for Class B-2 Concrete.

The #6-H400 bars are lapped with the #6-H401 bars with a minimum lap of 3'-11". The contractor may use a mechanical bar splice in lieu of a lap splice. When a mechanical bar splice is used, the actual bar segment length will be determined by the contractor to accommodate manufacturer's recommendations for installation and ease of construction. The cost of furnishing and installing the bar splices will be considered completely covered by the contract unit price for Reinforcing Steel (Galvanized). No adjustment of the quantity of reinforcing steel will be allowed for the use of mechanical bar splices.

Cost of field drilling holes in existing plate girder webs will be considered completely covered by the contract unit price for Class B-2 Concrete.


SECTION NEAR END BENT

END BENT NO. 4

Detailed May 2025
Checked May 2025

Note: This drawing is not to scale. Follow dimensions.


Sheet No. 4 of 17




MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)

DATE	DESCRIPTION




ELEVATION OF WING




DETAIL A


ELEVATION OF END BENT




PLAN OF END BENT



ELEVATION OF WING
OPTIONAL TURNED DRAIN
(Use only when straight drain is not practical.)



PART PLAN



PART SECTION A-A
(Section thru wing similar)

General Notes:

- All drain pipe shall be sloped 1 to 2 percent.
- Drain pipe may be either 6-inch diameter corrugated metallic-coated steel pipe, underdrain, 4-inch diameter corrugated polyvinyl chloride (PVC) drain pipe, or 4-inch diameter corrugated polyethylene (PE) drain pipe.
- Drain pipe shall be placed at fill face of end bent and inside face of wings. The pipe shall slope to lowest grade of ground line, also missing the lower beam of end bent by a minimum of 1 1/2 inches.
- Perforated pipe shall be placed at fill face side and inside face of wings at the bottom of end bent and plain pipe shall be used where the vertical drain ends to the exit at ground line.


VERTICAL DRAIN AT END BENTS

End Bent No. 4 shown, End Bent No. 1 similar.
Note: This drawing is not to scale. Follow dimensions.

Detailed May 2025
Checked May 2025

Note: This drawing is not to scale. Follow dimensions.

Sheet No. 6 of 17




DATE PREPARED	10/7/2025
ROUTE	1-49
STATE	MO
DISTRICT	BR
SHEET NO.	6
COUNTY	VERNON
JOB NO.	JSR0064
CONTRACT ID.	
PROJECT NO.	
BRIDGE NO.	A17751

DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION



105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)



PART PLAN OF STRUCTURAL STEEL

PHASES OF WORK

Prior to Heat Straightening:


1. Complete surface preparation of existing steel that will be subjected to Non-Destructive Testing (NDT) or heat from the heat straightening process.
2. Remove the intermediate diaphragms and connection plates as indicated in the plans or directed by the engineer. As approved by the engineer, existing connection plates may be re-used. Non-Destructive Testing (NDT) of the connection plate welds are required to assure suitability for re-use; paint shall be removed prior to any NDT of welds. Existing connection plates not re-used shall be removed and the girders ground smooth.
3. Inspect girder in the area of repair for cracks by any non-destructive means. If cracks are identified, repair cracks as directed by the engineer.

Heat Straightening:

1. Heat straighten girders covering the length of the collision damaged girders. The girders shall be heat straightened to remove web and bottom flange twisting. See Special Provisions.
 2. The shoulder and adjacent lane of I-49 shall remain closed, and no traffic shall be allowed over the girder(s) being straightened during the heat straightening process.
 3. MoDOT has concerns about heat straightening through a splice location. Please consult your heat straightening subcontractor as you prepare your bid.
- Post Heat Straightening:**
1. Install new connection plates and diaphragms.
 2. Recoat girders over the length of damage and where paint was removed during the heat straightening process with System G (Gray).
 3. Paint new diaphragms and connection plates with System G (Gray).


Girder No.	Dim. A	Dim. B
4	2"	*
5	2"	*

* Value to be determined by contractor



DETAIL OF GIRDER SHOWING IMPACT DAMAGE

- (1) Approximate collision impact zone and limits of required heat straightening.
- (2) Approximate girder sweep at point of impact
- (3) Approximate vertical distortion of bottom flange



STATE OF MISSOURI
Professional Engineer
No. 10000
PC-20220078

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION



105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)

DATE: _____

DESCRIPTION: _____

PROJECT NO. _____

BRIDGE NO. _____

A17751

COUNTY: _____

JOB NO.: _____

VERNON

JSR0064

CONTRACT ID. _____

ROUTE: 1-49


STATE: MO

DISTRICT: _____


BR: 8

DATE PREPARED: 10/7/2025


MOE-20190078




TYPICAL PART SECTION NEW
INTERMEDIATE DIAPHRAGMS



DETAIL A
(Bottom flange shown,
top flange similar.)




DETAIL B



OPTIONAL
DETAIL B

* At the contractor's option, rectangular fill plates may be used in lieu of diamond fill plates as shown in Optional Detail B.



DETAIL OF NEW CONNECTION PLATES
(Longitudinal stiffener(s) not shown for clarity.)

- (1) Tight fit
- (2) Weld to compression flange as located on Part Plan of Structural Steel.
- * Typical for all intermediate web stiffeners, intermediate diaphragm connection plates and bearing stiffeners.

Notes:

See Sheet No. 8 for phases of work.

Girders No. 4 & 5 shall be heat straightened to remove web and bottom flange twisting. Cost will be considered completely covered by the contract lump sum price for Heat Straightening. See Special Provisions.

Limits of collision damage vary by girder. Field verify locations and limits of collision damage requiring repairs.

Estimated limits of new System G Coating are equivalent to approximate limits of heat straightening.

The cost of non-destructive testing for connection plate welds evaluated for re-use will be considered completely covered by the contract lump sum price for Non-Destructive Testing. All other Non-Destructive Testing will be completely covered by the contract lump sum price for Heat Straightening.

Remove existing diaphragms and their connection plates to girders per the locations shown. Grind smooth remnants of plates and weldment.

Remove diaphragms and lateral bracing within limits of required Heat Straightening as needed. If removed, replace in kind.

The cost of removing existing diaphragms, connection plates and removal of weld metal with the process of grinding will be considered completely covered by the contract unit price for Removal of Diaphragm (See Special Provisions).

The cost of furnishing and installing new diaphragm, connection plates and intermediate stiffeners will be considered completely covered by the contract unit price for Fabricated Structural Carbon Steel (Misc.). Quantity for Fabricated Structural Carbon Steel (Misc.) includes the weight of connection plates to girders and the steel angles that make up the diaphragm. Filler plates and other materials shall be considered subsidiary to the contract unit price for Fabricated Structural Carbon Steel (Misc.).

Contact surfaces shall be in accordance with Sec 1081 for surface preparation. Contractor may field drill holes with the approval of the Engineer to facilitate construction.

All longitudinal dimensions are parallel to grade.



ROUTE 1-49
STATE MO
DISTRICT 9
SHEET NO.

COUNTY VERNON
JOB NO. JSR0064
CONTRACT ID.


PROJECT NO.
BRIDGE NO. A17751

DATE	DESCRIPTION


MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION




105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)




PART ELEVATION OF LEFT (MEDIAN SIDE) BARRIER
SHOWING DRAINAGE SYSTEM



SECTION B-B



SECTION A-A



PART ELEVATION OF MEDIAN END
OF INT. BENT NO. 3
(Int. Bent No. 2 similar)

Notes:
Standard Pipe Hangers shall be placed along \varnothing 10" \varnothing Collector Pipe, offset 16 1/2" \pm from \varnothing Exterior Girder and spaced longitudinally as shown in Elevation.
For materials and construction requirements of Drainage System, see Job Special Provisions.
For location of slab drains see Sheet No. 10.

DRAINAGE SYSTEM ON STRUCTURE

Detailed May 2025
Checked May 2025

Note: This drawing is not to scale. Follow dimensions.

Sheet No. 11 of 17



ROUTE 1-49
STATE MO
DISTRICT
SHEET NO. 11

COUNTY VERNON

JOB NO. JSR0064

CONTRACT ID.


PROJECT NO.

BRIDGE NO. A17751


DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION


105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)




PART ELEVATION OF LEFT CURB AT END BENT NO. 4



PART PLAN



SECTION D-D



SECTION E-E

Notes:

Payment for all concrete and reinforcement for barrier replacement at End Bent No. 4, complete in place, will be considered completely covered by the contract unit price for Remove and Replace Barrier.

Ends of existing longitudinal reinforcement in curb and parapet may be trimmed as necessary to maintain 1 1/2" clearance to end of curb blockout.


* Seal joint with sealant in accordance with Sec 717 for silicone joint sealant for saw cut and formed joints.

BARRIER REPLACEMENT AT END BENT NO. 4
(Left curb shown, right curb similar)

Detailed May 2024
Checked May 2025

Note: This drawing is not to scale. Follow dimensions.

Sheet No. 13 of 17




DATE PREPARED	10/7/2025
ROUTE	I-49
STATE	MO
DISTRICT	BR
SHEET NO.	13
COUNTY	VERNON
JOB NO.	JSR0064
CONTRACT ID.	
PROJECT NO.	
BRIDGE NO.	A17751

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION




105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)


DATE	DESCRIPTION




ELEVATION SHOWING REINFORCEMENT
(Right End Post at End Bent No. 4 similar)




PLAN SHOWING REINFORCEMENT
LEFT END POST AT END BENT NO. 1




SECTION A-A




SECTION B-B



ELEVATION SHOWING REINFORCEMENT
(Right End Post at End Bent No. 1 similar)




PLAN SHOWING REINFORCEMENT
LEFT END POST AT END BENT NO. 4



PART ELEVATION SHOWING END POST
CONCRETE REMOVAL

Cost of removing existing end posts will be considered completely covered by the contract unit price for Curb Blockout.

- Notes:
- Work this sheet with Sheet No. 12.
 - For details of resin anchors, see Sheet No. 12.
 - Resin anchors shall be shifted or bent in field to clear one-inch diameter holes by at least 1/2 inch.





DETAILS OF END POST AND
GUARD RAIL ATTACHMENT

Detailed May 2024
Checked May 2025


Note: This drawing is not to scale. Follow dimensions.

CURB BLOCKOUT AT END BENTS

 <p>MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION</p> <p>105 WEST CAPITOL JEFFERSON CITY, MO 65102 1-888-ASK-MODOT (1-888-275-6636)</p>	DATE	DESCRIPTION
 <p>STATE OF MISSOURI MICHAEL J. VERNON PROFESSIONAL ENGINEER No. 20200778 MO-PE-2012000778 DATE PREPARED 10/7/2025 ROUTE I-49 STATE MO DISTRICT BR 14 COUNTY VERNON JOB NO. JSR0064 CONTRACT ID. PROJECT NO. BRIDGE NO. A17751</p>		




PART PLAN SHOWING REINFORCEMENT




SECTION B-B

SECTION A-A


SECTION C-C




UNDERSEAL ACCESS HOLE DETAIL (If required)




CONSTRUCTION JOINT DETAIL



DETAIL A (END BENT NO. 1)




SECTION BETWEEN CURB AND BARRIER



SECTION THRU JOINT AT END OF BRIDGE APPROACH SLAB


SKEW = 50° 32' L.A.

Extend seal full width of approach slab.



SECTION C-C

BRIDGE APPROACH SLAB (MAJOR)



DETAILS OF TIMBER HEADER

Remove timber header when concrete pavement is placed.

General Notes:

- All concrete for the bridge approach slab and sleeper slab shall be in accordance with Sec 503 (f'c = 4,000 psi).
- The reinforcing steel in the bridge approach slab and the sleeper slab shall be epoxy coated Grade 60 with fy = 60,000 psi.
- Drain pipe may be either 6" diameter corrugated metallic-coated pipe, underdrain, 4" diameter corrugated polyvinyl chloride (PVC) drain pipe, or 4" diameter corrugated polyethylene (PE) drain pipe.
- Minimum clearance to reinforcing steel shall be 1 1/2", unless otherwise shown.
- The reinforcing steel in the bridge approach slab and the sleeper slab shall be continuous. The transverse reinforcing steel may be made continuous by providing a minimum lap splice of 29 inches for #5 bars and 44 inches for #6 bars, or by mechanical bar splice.
- Mechanical bar splices shall be in accordance with Sec 710.
- All joint filler shall be in accordance with Sec 1057 for preformed fiber expansion joint filler except as noted.

The contractor shall pour and satisfactorily finish the bridge slab before placing the bridge approach slab.

Longitudinal construction joints in approach slab and sleeper slab shall be aligned with longitudinal construction joints in bridge slab.

For concrete approach pavement details, see roadway plans.

See Missouri Standard Plan 609.00 for details of Type A curb.

Payment for furnishing all materials, labor and excavation necessary to construct the approach slab, including the timber header, sleeper slab, underdrain, Type 5 aggregate base, joint filler and all other appurtenances and incidental work as shown on this sheet, complete in place, will be considered completely covered by the contract unit price for Bridge Approach Slab (Major) per square yard.

* Seal joint between vertical face of approach slab and wing with sealant in accordance with Sec 717 for silicone joint sealant for saw cut and formed joints.

Open cell foam joint seal width shall be 4" and depth shall be determined by the manufacturer. Manufacturer recommended seal shall meet the movement and installation gap requirements and skew effect.




The open cell foam joint seal shall be installed according to the manufacturer's recommendations.

The Open Cell Foam Joint Seal, complete in place, will be considered completely covered by the contract unit price for Bridge Approach Slab (Major).

STATE OF MISSOURI	
Professional Engineer	
12010025 11:28 AM	MOE-20120072
DATE PREPARED	12/1/2025
ROUTE	I-49
STATE	MO
DISTRICT	BR
SHEET NO.	15
COUNTY	VERNON
JOB NO.	JSR0064
CONTRACT ID.	
PROJECT NO.	
BRIDGE NO.	A17751
DATE	
DESCRIPTION	

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION



105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)



Finished Bend Diameters D and Hook Dimensions

Standard Pin Bend Shapes					
Size Case	D	A or G	H	J	
#4	1	3"	8"	6"	4"
#5	1	3 3/4"	10"	7"	5"
#6	1	4 1/4"	12"	8 1/4"	6"
#7	2	5 1/4"	14"	9 3/4"	7"
#8	2	6"	16"	11"	8"
#9	1	9 1/4"	17"	13 1/4"	10"
#10	1	10 1/4"	22"	17 1/2"	13 1/4"
#11	1	12"	24 1/2"	19 1/2"	14 7/8"
#14	1	18 1/2"	31 1/2"	27 1/2"	21 5/8"
#18	1	24"	41 1/2"	36 1/4"	28 1/2"

Stirrup Pin Bend Shapes (S)					
Size Case	D	A or G	H	J	
#4	2	4 1/4"	4 1/4"	5"	3"
#5	3	5"	5 1/4"	6"	4"
#6	1	4 1/4"	5 3/4"	5 3/4"	3 3/4"
#6	3	3 3/4"	6 1/4"	7"	3 3/8"
#6	1	4 1/4"	12"	7 3/4"	4 3/8"



BENDING DIAGRAMS

Size	Reinforcing Steel Totals (Pounds)			
	Substructure	Slab	Barrier	Slip Form
WS	0	0	0	0
4	0	0	0	0
5	0	2,584	3,582	0
6	0	1,450	0	0
7	0	0	0	0
8	0	0	0	0
9	0	0	0	0
10	0	0	0	0
11	0	0	0	0
14	0	0	0	0
18	0	0	0	0
By Type	0	4,034	3,582	0
Entire Bridge				7,616

ALL superstructure reinforcing steel shall be galvanized unless otherwise specified. Products used to repair damaged zinc coating shall not contain aluminum.


All dimensions are out to out. Shapes ending with an S shall be bent in accordance with stirrup pin bend shapes. Unless otherwise noted, finished bending diameter D is the same for all bends of a shape. (1) Shall be a deformed or plain spiral bar or wire. Four angle or channel spacers are required for each column spiral. Spacers are to be placed on inside of spirals. Length and weight of column spirals do not include splices or spacers.

BENDING DIAGRAMS AND REINFORCING STEEL TOTALS

Detailed May 2025
Checked May 2025

Note: This drawing is not to scale. Follow dimensions.

Sheet No. 16 of 17




ROUTE	I-49
STATE	MO
DISTRICT	BR
SHEET NO.	16
DATE PREPARED	10/7/2025
COUNTY	VERNON
JOB NO.	JSR0064
CONTRACT ID.	
PROJECT NO.	
BRIDGE NO.	A17751

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)


U.I.P. AND REHABILITATE EXISTING (64'-128'-64')
CONTINUOUS COMPOSITE PLATE GIRDER SPANS (SKEW: 50°32'00" L.A.)

38'-0"± Roadway




TYPICAL SECTION THRU EXISTING DECK


PART ELEVATION SHOWING
PLUGGING OF CURB OUTLETS




Notes:
Proposed 1 3/4" Latex Modified Concrete Wearing Surface not shown for clarity.
Cost of labor and materials required to plug existing curb outlets will be considered completely covered by the contract unit price for Curb Blockout.
Estimated material required to fill all curb outlets is 1.1 cubic yards (for information only).




MONOLITHIC DECK REPAIR




MONOLITHIC DECK REPAIR
REQUIRING INCIDENTAL FORMING




REMOVAL OF EXISTING DECK
REPAIR BEFORE HYDRO DEMOLITION



MONOLITHIC DECK REPAIR
REQUIRING FULL DEPTH REPAIR



TYPICAL ELEVATION OF
INT. BENTS NO. 2 & 3



DETAIL A

- (1) Removal of existing 3/8"± wearing surface plus 1/2" of existing deck
- (2) 1/2" minimum total surface hydro demolition of sound concrete, measured to mortar line
- (3) 1" vertical side shall be established outside the deteriorated area.
- (4) 1 3/4" minimum Latex Modified Concrete wearing surface
- (5) Original depth of deck minus previous scarification

REPAIRS TO BRIDGE: 1-49 NB OVER ROUTE K


ROUTE 1-49 NB FROM ROUTE E TO ROUTE 54
ABOUT 1.1 MILES SOUTH OF ROUTE 54
BEGINNING STATION 867+82.00± (Match Existing)

Detailed May 2025
Checked May 2025

Note: This drawing is not to scale. Follow dimensions.

Sheet No. 1 of 15

SEC/SUR 2/11 TWP 35N RGE 31W



ROUTE 1-49
STATE MO
DISTRICT BR
SHEET NO. 1

PROJECT NO.
BRIDGE NO. A17752

DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)

General Notes:

Design Specifications:
 2002 ASHTO LFD (17th Ed.) Standard Specifications
 Bridge Deck Rating = 5
 Design Loading:
 HS20-44 (1965 & New Construction)

Design Unit Stresses:
 Class B-2 Concrete (Full Depth Repair & End Bent) $f'c = 4,000$ psi
 Class B-1 Concrete (Curb Blockout) $f'c = 4,000$ psi
 Reinforcing Steel (ASTM A615 Grade 60) $f_y = 60,000$ psi

Recoating Existing Steel:

Protective Coating: System G in accordance with Sec 1081.
 Surface Preparation: Surface preparation of the existing steel shall be in accordance with Sec 1081 for Recoating of Structural Steel (System G) with Inorganic Zinc Primer. The cost of surface preparation will be considered completely covered by the contract lump sum price for Surface Preparation for Recoating Structural Steel.

Prime Coat: The cost of the prime coat will be considered completely covered by the contract lump sum price for Field Application of Inorganic Zinc Primer.

Field Coat(s): The color of the field coat(s) shall be Gray (Federal Standard #26373). The cost of the intermediate field coat will be considered completely covered by the contract lump sum price for Intermediate Field Coat (System G). The cost of the finish field coat will be considered completely covered by the contract lump sum price for Finish Field Coat (System G).

Limits of Paint Overlap: System G shall overlap the existing coating between 6 inches and 12 inches in order to achieve maximum coverage at the paint limit of each complete system. The final field coating shall be masked to provide crisp, straight lines and to prevent overspray beyond the overlap required.

Miscellaneous:

The existing vertical clearance shall be maintained during construction when Route K is open to traffic.

Lane closures on Route I-49 and Route K shall be in accordance with traffic control plans.

Outline of existing work is indicated by light dashed lines. Heavy lines indicate new work.

All existing dimensions shown were taken from as-built drawings, or limited field measurements. Contractor shall verify all dimensions in field.

Roadway surfacing adjacent to bridge ends shall match new bridge wearing surface (Roadway item).

All joint filler shall be in accordance with Sec 1057 for preformed sponge rubber expansion and partition joint filler, except as noted.

Minimum clearance to reinforcing steel shall be 1 1/2", unless otherwise shown.

Bars bonded in existing concrete not removed shall be cleanly stripped and embedded into new concrete where possible. If length is available, existing bars shall extend into new concrete at least 40 diameters for plain bars and 30 diameters for deformed bars, unless otherwise noted.

In order to maintain grade and a minimum thickness of wearing surface as shown on plans it may be necessary to use additional quantities of wearing surface at various locations throughout the structure. The cost of furnishing and installing the wearing surface will be considered completely covered in the contract unit price, including all additional labor, materials or equipment for variations in thickness of wearing surface.

Substructure Repair:

Provide a minimum 1 1/2-inch clear cover to existing reinforcing steel when forming substructure repair at columns.

All concrete repairs shall be in accordance with Sec 704 unless otherwise noted.

Traffic Handling:


Structure to be closed during construction. See roadway plans for traffic control.

Estimated Quantities

Item		Total
** Removal of Miscellaneous ACM (Non-Friable)	sq. foot	28
Total Surface Hydro Demolition	sq. yard	1083
Removal of Asphalt Wearing Surface	sq. foot	9747
Removal of Existing Deck Repair	sq. foot	500
Partial Removal of Substructure Concrete	linear foot	1
Removal of Existing Expansion Joint & Adjacent Concrete	each	60
Removal of Existing Bearings	each	5
Remove and Replace Barrier	linear foot	9
Bridge Approach Slab (Major)	sq. yard	170
Supplementary Wearing Surface Material	cu. yard	18
Late Modified Concrete Wearing Surface	sq. yard	1085
Diamond Grinding	sq. yard	1085
Class B-2 Concrete	cu. yard	72.9
Curb Blockout	linear foot	588
Substructure Repair (Formed)	sq. foot	50
Full Depth Repair	sq. foot	500
Cleaning and Epoxy Coating	sq. foot	1856
Reinforcing Steel (Galvanized)	pounds	4030
Protective Coating - Concrete Bents and Piers (Epoxy)	linear foot	1
Drainage System (On Structure)	linear foot	1
Surface Preparation for Recoating Structural Steel	sq. foot	1500
Field Application of Inorganic Zinc Primer	sq. foot	1500
Intermediate Field Coat (System G)	sq. foot	1500
Finish Field Coat (System G)	sq. foot	1500
Cored Slab Drains	each	37
Vertical Drain at End Bents	each	2
Laminated Neoprene Bearing Pad Assembly	each	5
Misc. Installation of Bearings (pre-owned)	each	5

* Supplementary wearing surface material will be paid for at the fixed unit price in accordance with Sec 109.

** Cost of removal of aluminum tube railing will be considered completely covered by the contract unit price for Removal of Miscellaneous ACM (Non-Friable).




DATE PREPARED
 10/7/2025
 ROUTE
 1-49
 STATE
 MO
 DISTRICT
 BR
 COUNTY
 VERNON
 JOB NO.
 JSR0064
 CONTRACT ID.

PROJECT NO.
 BRIDGE NO.
 A17752

DATE	DESCRIPTION


MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL
 JEFFERSON CITY, MO 65102
 1-888-ASK-MODOT (1-888-275-6636)



U bars and slab reinforcement not shown for clarity.


SECTION NEAR END BENT



(1) 2 Spa. @ 12"


PART PLAN

Slab reinforcement and resin anchors not shown for clarity.
Above dimensions taken along \mathcal{C} of existing bearing
from outside face of proposed slab.



All dimensions are plus/minus.

DETAIL C



All dimensions are plus/minus.

DETAIL D

Notes:
Work this Sheet with Sheet No. 5.

The exposed and accessible surface of the existing structural steel and bearing that will be encased in concrete shall be cleaned with a minimum of SSPC-SP-3 surface preparation and coated with a minimum of one coat of gray epoxy-mastic primer (non-aluminum) in accordance with Sec. 1081 to produce a dry fill thickness of not less than 3 mils before concrete is poured. The surface preparation and coating for girders shall extend a minimum of one foot outside the face of the beam encasement. Payment for cleaning and coating steel to be encased in concrete will be considered completely covered by the contract unit price for Class B-2 Concrete.

The #6-H400 bars are lapped with the #6-H401 bars with a minimum lap of 3'-1". The contractor may use a mechanical bar splice in lieu of a lap splice. When a mechanical bar splice is used, the actual bar segment length will be determined by the contractor to accommodate manufacturer's recommendations for installation and ease of construction. The cost of furnishing and installing the bar splices will be considered completely covered by the contract unit price for Reinforcing Steel (Galvanized). No adjustment of the quantity of reinforcing steel will be allowed for the use of mechanical bar splices.


Cost of field drilling holes in existing plate girder webs will be considered completely covered by the contract unit price for Class B-2 Concrete.

END BENT NO. 4

Detailed May 2025
Checked May 2025

Note: This drawing is not to scale. Follow dimensions.

Sheet No. 4 of 15




DATE PREPARED	10/7/2025
ROUTE	I-49
STATE	MO
DISTRICT	
SHEET NO.	4
COUNTY	VERNON
JOB NO.	JSR0064
CONTRACT ID.	
PROJECT NO.	
BRIDGE NO.	A17752


DATE	DESCRIPTION

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION


105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)




PART SECTION NEAR DRAIN




PART PLAN OF SLAB AT DRAIN




PART SECTION SHOWING BRACKET ASSEMBLY




ELEVATION OF DRAIN



PLAN OF DRAIN



PLAN OF OPTIONAL FRP DRAIN



PART PLAN SHOWING CORED SLAB DRAIN LOCATIONS

CORED SLAB DRAINS

General Notes:


Contractor shall have the option to construct either steel or FRP slab drains. All drains shall be of same type. Slab drain bracket assembly shall be ASTM A709 Grade 36 steel. The bracket assembly shall be galvanized in accordance with ASTM A123. All bolts, hardened washers, lock washers and nuts shall be galvanized in accordance with AASHTO M232 (ASTM A153), Class C. All 1/2-inch diameter bolts shall be ASTM A507, except as noted. Shop drawings will not be required for the slab drains and the bracket assembly. Cost of cored slab drains, complete in place, will be considered completely covered by the contract unit price for Cored Slab Drain per each. Holes for slab drains shall be cored. Percussion drilling will not be permitted. Slab drain locations may be shifted the minimum extent necessary to avoid slab reinforcement and to allow for field drilling bolt hole in web of existing beam for bracket assembly attachment. Cored slab drains shall be placed vertically. For details of plugging existing curb outlets, see Sheet No. 1.

Notes for Steel Drain:

The drains shall be galvanized in accordance with ASTM A123. Drains shall be inserted through slab such that damage to galvanized coating is minimized.

Notes for FRP Drain:

Drains shall be machine filament-wound thermosetting resin tubing meeting the requirements of ASTM D2996 with the following exceptions: Minimum reinforced wall thickness shall be 1/4 inch. The resin used shall be ultraviolet (UV) resistant and/or have UV inhibitors mixed throughout. Drains may have an exterior coating for additional UV resistance. Care shall be taken to avoid damage to exterior coating during installation. The color of the slab drain shall be gray (Federal Standard 26373). The color shall be uniform throughout the resin and any coating used. The combination of materials used in the manufacture of the drains shall be tested for UV resistance in accordance with ASTM D4329 Cycle A. The representative material shall withstand at least 300 hours of testing with only minor discoloration and without any physical deterioration. The contractor shall furnish the results of the required ultraviolet testing prior to acceptance of the slab drains. At the contractor's option, drains may be field cut. The method of cutting FRP slab drains shall be as recommended by the manufacturer to ensure a smooth, chip-free cut.



MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)

DATE: _____ DESCRIPTION: _____

BRIDGE NO. A17752

PROJECT NO. _____

JOB NO. JSR0064

CONTRACT ID. _____

ROUTE 1-49 MO


DATE PREPARED 10/7/2025

DISTRICT 8


COUNTY VERNON

STATE MO


BR 8




PART ELEVATION OF RIGHT (MEDIAN) BARRIER
SHOWING DRAINAGE SYSTEM



SECTION B-B



SECTION A-A



PART ELEVATION OF MEDIAN END
OF INT. BENT NO. 3
(Int. Bent No. 2 similar)

Notes:
Standard Pipe Hangers shall be placed along \varnothing 10" \varnothing Collector Pipe, offset 16 1/2" \pm from \varnothing Exterior Girder and spaced longitudinally as shown in Elevation.
For materials and construction requirements of Drainage System, see Job Special Provisions.
For location of slab drains see Sheet No. 8.

DRAINAGE SYSTEM ON STRUCTURE

Detailed May 2025
Checked May 2025

Note: This drawing is not to scale. Follow dimensions.

Sheet No. 9 of 15









MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION



105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)


DATE	DESCRIPTION



DETAILS OF RESIN ANCHORS

(1) Manufacturer's recommended embedment length (5 inches minimum).


PART ELEVATION AT FORMED JOINT



ELEVATION OF LEFT CURB BLOCKOUT

(Right curb blockout similar)
Longitudinal dimensions are along grade and are taken at top outside edge of parapet.

SECTION THRU SAW CUT JOINT



SECTION A-A

SECTION B-B

PART ELEVATION OF CURB BLOCKOUT

CURB BLOCKOUT


Notes:

- * Slip-formed option only.
- Conventional forming or slip forming may be used. Saw cut joints may be used with conventional forming.
- Bridge rail not shown for clarity.
- Concrete in curb blockout shall be Class B-1.
- Measurement of curb blockout is to the nearest linear foot, measured at the top outside edge of parapet. (Match existing curb and parapet)
- All exposed edges of curb blockout shall have either a 1/2-inch radius or 3/8-inch bevel, unless otherwise noted.
- Payment for concrete, reinforcement, resin anchor systems and any other work incidental to the curb blockout, complete in place, will be considered completely covered by the contract unit price for Curb Blockout per linear foot.
- Cost of any concrete curb or parapet repair will be considered completely covered by the contract unit price for Curb Blockout.
- All curb blockout reinforcement shall be epoxy coated.
- (2) Shift resin anchors where necessary to clear existing anchor bolts for bridge rail, miss curb outlets (if present) and clear existing reinforcement.
- Use a minimum lap of 3'-1" for #5 horizontal curb blockout bars.
- Concrete traffic barrier delineators shall be placed on top of the curb blockout similarly as shown on Missouri Standard Plans 617.10 and in accordance with Sec 617. Delineators on bridges with two-lane, two-way traffic shall have retro-reflective sheeting on both sides. Concrete traffic barrier delineators will be considered completely covered by the contract unit price for Curb Blockout.
- The contractor shall use one of the qualified resin anchor systems in accordance with Sec 1039.
- The minimum embedment depth in concrete with $f'c = 4,000$ psi for the resin anchor system shall be that required to meet the minimum ultimate pullout strength in accordance with Sec 1039 but shall not be less than 5 inches.
- A galvanized #5 Grade 60 reinforcing bar shall be substituted for the 5/8" threaded rod.
- For slip-formed option, both sides of the curb blockout shall have a vertically broomed finish and the top shall have a transversely broomed finish.

Detailed May 2025
Checked May 2025

Note: This drawing is not to scale. Follow dimensions.

Sheet No. 10 of 15




ROUTE	1-49
STATE	MO
DISTRICT	BR
SHEET NO.	10
COUNTY	VERNON
JOB NO.	JSR0064
CONTRACT ID.	
PROJECT NO.	
BRIDGE NO.	A17752


MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)


DATE	DESCRIPTION




PART ELEVATION OF LEFT CURB AT END BENT NO. 4



PART PLAN



SECTION D-D



SECTION E-E

- Notes:
- Payment for all concrete and reinforcement for barrier replacement at End Bent No. 4, complete in place, will be considered completely covered by the contract unit price for Remove and Replace Barrier.
 - Ends of existing longitudinal reinforcement in curb and parapet may be trimmed as necessary to maintain 1 1/2" clearance to end of curb blockout.
 - * Seal joint with sealant in accordance with Sec 717 for silicone joint sealant for saw cut and formed joints.


BARRIER REPLACEMENT AT END BENT NO. 4

(Left curb shown, right curb similar)

Detailed May 2024
Checked May 2025

Note: This drawing is not to scale. Follow dimensions.

Sheet No. 11 of 15




DATE PREPARED	10/7/2025
ROUTE	I-49
STATE	MO
DISTRICT	BR
SHEET NO.	11
COUNTY	VERNON
JOB NO.	JSR0064
CONTRACT ID.	
PROJECT NO.	
BRIDGE NO.	A17752

DATE	DESCRIPTION


MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION




105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)




ELEVATION SHOWING REINFORCEMENT
(Right End Post at End Bent No. 4 similar)




SECTION A-A




LEFT END POST AT END BENT NO. 1




SECTION B-B



ELEVATION SHOWING REINFORCEMENT
(Right End Post at End Bent No. 1 similar)




LEFT END POST AT END BENT NO. 4



PART ELEVATION SHOWING END POST
CONCRETE REMOVAL

Cost of removing existing end posts will be considered completely covered by the contract unit price for Curb Blockout.

- Notes:
- Work this sheet with Sheet No. 10.
 - For details of resin anchors, see Sheet No. 10.
 - Resin anchors shall be shifted or bent in field to clear one-inch diameter holes by at least 1/2 inch.






DETAILS OF END POST AND
GUARD RAIL ATTACHMENT

Detailed May 2024
Checked May 2025

Note: This drawing is not to scale. Follow dimensions.

CURB BLOCKOUT AT END BENTS



<p>MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION</p> <p>105 WEST CAPITOL JEFFERSON CITY, MO 65102 1-888-ASK-MODOT (1-888-275-6636)</p>		<p>DATE</p> <p>DESCRIPTION</p>
		<p>BRIDGE NO. A17752</p> <p>PROJECT NO.</p> <p>CONTRACT ID. JSR0064</p> <p>JOB NO. VERNON</p> <p>COUNTY MO</p> <p>ROUTE 1-49</p> <p>DATE PREPARED 10/7/2025</p> <p>DESIGNED BY MCHES/12000778</p> <p>DISTRICT BR 12</p>



Finished Bend Diameters D and Hook Dimensions

Standard Pin Bend Shapes					
Size Case	D	A or G	H	J	
#4	1	3"	8"	6"	4"
#5	1	3 3/4"	10"	7"	5"
#6	1	4 1/4"	12"	8 1/4"	6"
#7	2	5 1/4"	14"	9 3/4"	7"
#8	2	6"	16"	11"	8"
#9	3	8"	17"	13 1/4"	10"
#10	1	9 1/4"	19 1/2"	15 1/2"	11 3/4"
#11	1	10 1/4"	22"	17 1/2"	13 1/4"
#14	1	12"	24 1/4"	19 1/4"	14 7/8"
#18	1	18 1/4"	31 1/4"	27 1/4"	21 5/8"
#18	1	24"	41 1/2"	36 1/4"	28 1/2"

Stirrup Pin Bend Shapes (S)					
Size Case	D	A or G	H	J	
#4	2	4 1/4"	4 1/4"	5"	3"
#5	3	5"	5 1/4"	6"	4"
#6	4	6 1/4"	6 1/4"	7"	5"
#6	1	4 1/4"	12"	7 3/4"	4 3/8"



BENDING DIAGRAMS


Size	Reinforcing Steel Totals (Pounds)			
	Substructure	Slab	Barrier	Slip Form
WS	0	0	0	0
4	0	0	0	0
5	0	2,584	3,582	0
6	0	1,450	0	0
7	0	0	0	0
8	0	0	0	0
9	0	0	0	0
10	0	0	0	0
11	0	0	0	0
14	0	0	0	0
18	0	0	0	0
By Type	0	4,034	3,582	0

Size	Entire Bridge			
	Plain	Galv.	Plain	Galv.
WS	0	0	0	0
4	0	0	0	0
5	0	2,584	3,582	0
6	0	1,450	0	0
7	0	0	0	0
8	0	0	0	0
9	0	0	0	0
10	0	0	0	0
11	0	0	0	0
14	0	0	0	0
18	0	0	0	0
By Type	0	4,034	3,582	0

ALL superstructure reinforcing steel shall be galvanized unless otherwise specified. Products used to repair damaged zinc coating shall not contain aluminum.

All dimensions are out to out. (1) Shall be a deformed or plain spiral bar or wire. Shapes ending with an S shall be bent in accordance with stirrup pin bend shapes. Unless otherwise noted, finished bending diameter D is the same for all bends of a shape. Four angle or channel spacers are required for each column spiral. Spacers are to be placed on inside of spirals. Length and weight of column spirals do not include splices or spacers.

BENDING DIAGRAMS AND REINFORCING STEEL TOTALS



ROUTE	1-49
STATE	MO
DISTRICT	BR
SHEET NO.	14
DATE PREPARED	10/7/2025
COUNTY	VERNON
JOB NO.	JSR0064
CONTRACT ID.	
PROJECT NO.	
BRIDGE NO.	A17752

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL
JEFFERSON CITY, MO 65102
1-888-ASK-MODOT (1-888-275-6636)

