

TABLE OF CONTENTS

A. Construction Requirements

	MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION 105 W. CAPITOL AVE. JEFFERSON CITY, MO 65101 Phone (888) 275-6636
	OWN, Inc. 8455 College Boulevard, Overland Park, KS 66210 Certificate of Authority #000062 Consultant Phone (816) 777-0400
	If a seal is present on this sheet, JSP's has been electronically sealed and dated.
	JOB NO. JSR0060 Jasper County, MO Date Prepared: 10/8/2026

**Only the following items of the Job Special Provision (Bridge) are authenticated
by the seal: A**

A. CONSTRUCTION REQUIREMENTS

1.0 Description. This provision contains general construction requirements for this project.

2.0 Construction Requirements. The plans and the asbestos and lead inspection report(s) for the existing structure(s) are included in the contract in the bridge electronic deliverables zip file for informational purposes only.

2.1 In order to assure the least traffic interference, the work shall be scheduled so that a lane closure is for the absolute minimum amount of time required to complete the work. A lane shall not be closed until material is available for continuous construction and the contractor is prepared to diligently pursue the work until the closed lane is opened to traffic.

2.2 Qualified special mortar shall be a qualified rapid set concrete patching material in accordance with [Sec 704](#). A qualified rapid set concrete patching material will not be permitted for half-sole repair, deck repair with void tube replacement, full depth repair, modified deck repair and substructure repair (formed) unless a note on the bridge plans specifies that a qualified special mortar may be used.

2.3 Provisions shall be made to prevent any debris and material from falling into the waterway. If determined necessary by the engineer, any debris and material that falls into the waterway shall be removed as approved by the engineer at the contractor's expense.

2.4 Any damage sustained to the remaining structure as a result of the contractor's operations shall be repaired or the material replaced as approved by the engineer at the contractor's expense.

2.5 Provisions shall be made to prevent damage to any existing utilities. Any damage sustained to the utilities as a result of the contractor's operations shall be the responsibility of the contractor. All costs of repair and disruption of service shall be as determined by the utility owners and as approved by the engineer.

2.6 The contractor shall provide steel plates over any unprotected open excavation on the open lane during non-working hours and in areas where work is not active. The plates shall be 3/4 inch thick. The plates shall extend 12 to 18 inches each side of the opening and cover the full width of work. The contractor shall bevel all edges to a slope no steeper than 3H:1V. The driving surface shall be treated for skid resistance either by surface deformation or direct application of a friction course and delineated as shown in the plans. The plates shall be securely affixed to the adjacent pavement using concrete anchors or through bolts. The method of attachment shall be approved by the engineer. Any damage to the structure as a result of this work shall be repaired as approved by the engineer at the contractor's expense.

3.0 Method of Measurement. No measurement will be made.

4.0 Basis of Payment. Payment for the above described work will be considered completely covered by the contract unit price for other items included in the contract.